



**A STUDY AND DESIGN FOR THE MANUFACTURE OF A GESTURE CONTROLLED
LIFT**

BY

SUCCESS IMHOENEGAMHE

ENG1905704

IKPONMONSA BLESSED FORTUNE

ENG1905702

IMHANMUOKOR ANTHONY

ENG1905703

IRIBHOGBE DARLINGTON OYAKHILOME

ENG1905705

IROWA-CHRISTOPHER EKONADOSE

ENG1905707

**A PROJECT PRESENTED TO THE DEPARTMENT OF MECHATRONICS
ENGINEERING, FACULTY OF ENGINEERING, UNIVERSITY OF BENIN, BENIN
CITY, EDO STATE IN PARTIAL FULFILMENT OF THE REQUIREMENTS FOR THE
AWARD OF BACHELOR OF ENGINEERING (B.Eng.) IN MECHATRONICS
ENGINEERING**

JANUARY 2025

**A STUDY AND DESIGN FOR THE MANUFACTURE OF A GESTURE CONTROLLED
LIFT**

BY

SUCCESS IMHOENEGAMHE	ENG1905704
IKPONMONSA BLESSED FORTUNE	ENG1905702
IMHANMUOKOR ANTHONY	ENG1905703
IRIBHOGBE DARLINGTON OYAKHILOME	ENG1905705
IROWA-CHRISTOPHER EKONADOSE	ENG1905707

**A PROJECT PRESENTED TO THE DEPARTMENT OF MECHATRONICS
ENGINEERING, FACULTY OF ENGINEERING, UNIVERSITY OF BENIN, BENIN
CITY, EDO STATE IN PARTIAL FUFILMENT OF THE REQUIREMENTS FOR THE
AWARD OF BACHELOR OF ENGINEERING (B.Eng.) IN MECHATRONICS
ENGINEERING**

JANUARY 2025

CERTIFICATION

This is to certify that this project was carried out by the persons listed below, from the Department of Mechatronics Engineering, Faculty of Engineering, University of Benin, Benin City.

SUCCESS IMHOENEGAMHE	ENG1905704
IKPONMONSA BLESSED FORTUNE	ENG1905702
IMHANMUOKOR ANTHONY	ENG1905703
IRIBHOGBE DARLINGTON OYAKHILOME	ENG1905705
IROWA-CHRISTOPHER EKONADOSE	ENG1905707

Prof. D. I Igbinomwanhia
(Project Supervisor)

Date

Engr. Martins Osikhueme
(Project Coordinator)

Date

Prof. Sadjere Godwin
(Head of Department)

Date

DECLARATION

We, listed below hereby declare that the project work titled “**A STUDY AND DESIGN FOR THE MANUFACTURE OF A GESTURE-CONTROLLED LIFT**” is an original work done by us under the supervision of Prof. D. I. Igbinomwanhia. The work has not been submitted in candidature for any degree and is not concurrently being submitted for any other degree, to the best of my knowledge.

SUCCESS IMHOENEGAMHE (ENG1905704)

Date

IKPONMONSA BLESSED FORTUNE (ENG1905702)

IMHANMUOKOR ANTHONY (ENG1905703)

Date

**IRIBHOGBE DARLINGTON
OYAKHILOME (ENG1905705)**

Date

**IROWA-CHRISTOPHER EKONADOSE
(ENG1905707)**

Date

DEDICATION

We dedicate this project to God Almighty, our sufficiency; to our parents, for their unwavering support; to our Head of Department, Prof. Sadjere Godwin; to our Project Supervisor, Prof. D. I. Igbinomwanhia; to our friends and relatives, through whom God has provided support and contributions to our success thus far; and to the society we are committed to serving as engineers.

ACKNOWLEDGEMENT

We wish to express our heartfelt gratitude to everyone who has contributed to the successful completion of this research project.

First and foremost, we are deeply thankful to our project supervisor, Prof D. I Igbinomwanhia, for his unwavering support, invaluable guidance, and commitment in nurturing our research skills throughout this journey. His wisdom and expertise have been instrumental in shaping the quality and direction of this study. We are indeed grateful.

We would also like to extend our appreciation to our Head of Department, Prof. Sadjere Godwin, and to all our lecturers and non-academic staff, for their immense contribution, dedication, and support towards the successful completion of our academic pursuits.

We also wish to express our deepest love and appreciation to our parents, and our families, for their constant encouragement, unwavering support, and enduring belief in us.

ABSTRACT

This project presents the study and design of a full-scale gesture-controlled lift system that integrates advanced hardware and intelligent control strategies to achieve touch-free vertical transportation. Leveraging a PAJ7620 gesture sensor and an ESP32 microcontroller, the system interprets user hand gestures to control a robust motor/pulley mechanism designed to handle loads of up to 500 kg over a lift height of 10 meters. The design incorporates rigorous load calculations, safety features including emergency braking and limit switches, and a comprehensive structural framework built from high-strength steel and aluminum. Through extensive prototype development, testing, and optimization, the system demonstrated high reliability, efficient energy use, and ease of integration within existing lift infrastructures. This innovative approach not only enhances user accessibility and safety but also paves the way for future advancements in automated, gesture-based control systems in commercial and industrial applications.

TABLE OF CONTENTS

CERTIFICATION.....	iii
DECLARATION	iv
DEDICATION	v
ACKNOWLEDGEMENT.....	vi
ABSTRACT.....	vii
CHAPTER ONE - INTRODUCTION.....	1
1.1 Background of Study.....	1
1.2 Problem Statement.....	2
1.3 Aims and Objectives.....	3
1.3.1 Aims.....	3
1.3.2 Objectives.....	3
1.4 Significance of Study	4
1.5 Scope of Work.....	5
CHAPTER TWO – LITERATURE REVIEW	7
2.1 Operational Definition of Terms	7
2.1.1 Gesture Control.....	7
2.1.2 Lift (Elevator).....	7
2.1.3 Gesture-Controlled Lift.	7
2.1.4 Touchless Interface.	8
2.1.5 Biometric Data.	8
2.1.6 Machine Learning.....	8
2.1.7 Human–Computer Interaction (HCI).....	9
2.1.8 Sensor Fusion.	9
2.1.9 Usability.	9
2.1.10 Accessibility.....	9
2.1.11 Response Time (Latency).	10
2.1.12 Error Rate.....	10
2.1.13 System Robustness.	10
2.1.14 Multimodal Fusion.	10
2.1.15 Data Privacy and Security.	11
2.1.16 User Satisfaction.	11
2.1.17 Haptic Feedback.....	11

2.1.18 Interoperability.	11
2.2 Background	12
2.3 Significance	13
2.4 Gesture Recognition Technologies	13
2.4.1 Comparison of Sensor Types.....	14
2.4.2 Machine Learning Workflows	15
2.4.3 Feedback Mechanisms.....	16
2.5 Design Principles	17
2.5.1 Load-Bearing Calculations, Material Choices, and CAD Modeling.....	17
2.5.2 Redundancy Systems	18
2.5.3 Ergonomic Guidelines for Intuitive Gesture Libraries.....	19
2.6 Case Studies	20
2.6.1 Analysis of Gesture-Controlled Wheelchair Systems.....	20
2.6.2 Review of Gesture Control in Industrial Automation	21
2.7 Comparative SWOT Analysis: Gesture, Voice, and Touch Interfaces	22
2.8 Manufacturing Challenges	24
2.9 Future Trends.....	25
2.10 Ethical and Social Considerations	26
2.11 Cross-Domain Innovations	26
2.12 Cybersecurity Vulnerabilities in Gesture-Controlled Systems	27
2.13 Psychological Acceptance of Gesture Interfaces	27
2.14 Augmented Reality (AR) Integration for Enhanced Interaction.....	28
2.15 Global Market Dynamics and Adoption Barriers	28
2.16 Disaster Resilience in Gesture-Controlled Lift Systems	29
2.17 Blockchain for Secure Gesture Data Logging.....	29
2.18 Neuromorphic Engineering for Low-Power Gesture Recognition	30
2.19 Digital Twins for Predictive Gesture System Optimization.....	30
2.20 Interoperability with Smart Building Ecosystems	30
2.21 Post-Pandemic Urban Design and Gesture Interfaces.....	31
2.22 Enhancing Accessibility for Wheelchair Users and People with Disabilities.....	31
2.23 Voice-Activated Elevator Systems as a Complementary Approach.....	32
2.25 Economic Considerations and Market Trends in Gesture-Controlled Lift Systems.....	33
2.26 Maintenance, Lifecycle Management, and Upgradability.....	34

2.27 Emerging Trends in Machine Learning for Real-Time Gesture Recognition.....	34
2.28 Regulatory Frameworks and Standardization in Touchless Elevator Control.....	35
2.29 User Experience and Learning Curve in Gesture-Based Elevator Systems	35
2.30 Ethical and Social Implications of Touchless Control Systems.....	36
2.31 Factors of Safety	36
2.32 Future Research Directions and Challenges	37
CHAPTER THREE – METHODOLOGY.....	39
3.1 FEASIBILITY STUDIES	39
3.1.1 Materials	41
3.1.2 Methodology.....	42
3.3 CONCEPTUAL DESIGN CONSIDERATIONS	45
3.3.1 CONSIDERATIONS FOR THE GESTURE CONTROL MECHANISM	45
3.3.2 CONSIDERATIONS FOR THE LIFT STRUCTURE	54
3.3.3 Decision Matrix for Pneumatic Zigzag Lift vs. Motor/Pulley System	66
3.3.4 Decision Matrix for Gesture Recognition System	70
3.4. SELECTION OF CONCEPTS	73
3.4.1 LIFT STRUCTURE	73
3.4.2 GESTURE RECOGNITION AND CONTROL MECHANISM.....	73
3.4 DETAILED DESIGN.....	75
3.5.1 DESIGN CALCULATIONS.....	75
3.5 MANUFACTURING SPECIFICATION	97
3.6 CONSTRUCTION AND MANUFACTURING	102
CHAPTER FOUR – RESULTS AND DISCUSSION.....	106
4.1 Gesture Recognition Performance.....	106
4.2 Gesture Sensor Calibration and Testing.....	107
4.3 Motor Efficiency and Control System Responsiveness.....	108
4.2.1 Motor Efficiency and Control System Responsiveness	108
4.4 Discussion of Results	111
CHAPTER 5 - CONCLUSION AND RECOMMENDATION	113
5.1 Conclusion	113
5.2 Recommendations	113
5.3 Future Work and Implications	114
REFERENCES.....	115

APPENDIX.....	128
---------------	-----

TABLE OF FIGURES

Figure 3.1: Sideview of Pneumatic Zigzag Lift	55
Figure 3.2: Isometric view of Pneumatic Zigzag Lift	56
Figure 3.3: Image of Pneumatic Zigzag Lift.....	58
Figure 3.4: Isometric view of Motor and Pulley Lift System.....	60
Figure 3.5: Side view of Motor and Pulley Lift System.....	61
Figure 3.6: Image of Motor and Pulley Lift System	63
Figure 4.1: Fabricated structure of the model	109
Figure 4.2: Motor Efficiency and Control Response	110

LIST OF TABLES

Table 2.1: Comparative SWOT Analysis.....	22
Table 2.2: Safety Factors	36
Table 3.1: List of Materials	41
Table 3.2: Design Specification	44
Table 3.3: Decision Matrix for Lift Structure	67
Table 3.4: Design Matrix for Gesture Control.....	70
Table 3.5: Comparison of Load Calculations.....	78
Table 3.6: Summary of Motor Specifications.....	82
Table 3.7: Summary of Pulley and Rope Specifications.....	86
Table 3.8: Summary of Structural Design	90
Table 3.9: Summary of Brake System Specifications	93
Table 3.10: Summary of Acceleration and Deceleration.....	96
Table 3.11: Manufacturing Specification	97
Table 4.1: Gesture Sensor Calibration Results	108

CHAPTER ONE - INTRODUCTION

1.1 Background of Study

The evolution of vertical transportation systems has mirrored humanity's technological ambitions. From the steam-powered elevators of the 19th century to the AI-driven smart lifts of today, elevators have become indispensable in urban landscapes. However, the COVID-19 pandemic exposed critical vulnerabilities in traditional lift systems. Manual button inputs—once considered a harmless necessity—transformed into vectors for microbial transmission. Research has shown that elevator buttons in high-traffic areas such as hospitals and shopping malls can harbor significant levels of pathogens, including *Staphylococcus aureus* and SARS-CoV-2 (Otter et al., 2013; van Doremalen et al., 2020).

Gesture recognition technology emerged as a transformative solution for achieving touchless interaction. Originally popularized by devices such as Microsoft's Kinect (Shotton et al., 2011), gesture recognition has evolved into a robust tool for human-machine interaction in diverse applications—from smart home controls to vertical transportation systems. In gesture-controlled lifts, natural hand movements (e.g., swipes or holds) are captured by sensors and interpreted by machine learning algorithms, enabling users to select floors or open doors without physical contact.

Beyond hygiene, gesture-controlled systems address significant accessibility challenges. According to the World Health Organization and the World Bank (2011), approximately 15% of the global population lives with disabilities, yet many public buildings still fall short of accessibility standards. By substituting physical buttons with intuitive gesture commands, these

systems offer an inclusive alternative that empowers users with motor impairments to interact with elevators more independently.

The pursuit of energy efficiency further drives innovation in elevator systems. Traditional elevators may consume a substantial portion of a building's energy due to inefficiencies in manual operation and prolonged standby modes. Emerging technologies—such as AI-driven scheduling algorithms and regenerative drive systems—are being integrated into modern elevators to reduce energy consumption and support sustainability goals, including those outlined in the United Nations' Sustainable Development Goal 11 for Sustainable Cities and Communities. (Sustainable Cities and Communities).

1.2 Problem Statement

Traditional lift systems, while functional, face three interconnected challenges: hygiene risks, accessibility barriers, and energy inefficiency. These issues have been exacerbated by the post-pandemic emphasis on public health and the global push for sustainable infrastructure.

Hygiene remains a paramount concern. Elevator buttons in high-traffic buildings are touched by thousands of users daily, creating hotspots for microbial transmission. During the COVID-19 pandemic, surface contact was identified as a key transmission route, with SARS-CoV-2 surviving on plastic surfaces for up to 72 hours (van Doremalen et al., 2020). In some healthcare facilities, contaminated elevator buttons have been linked to increased rates of nosocomial infections (Kampf et al., 2020). While alternative solutions—such as voice activation and foot pedals—were explored, they introduced new challenges: voice systems often struggled with varied accents and background noise, and foot pedals posed tripping hazards for elderly users.

Accessibility is another critical issue. Manual buttons can exclude individuals with motor disabilities, perpetuating inequality in public spaces. A 2022 report by the World Health Organization highlighted that a substantial number of wheelchair users avoid multi-story buildings due to the lack of accessible elevator designs (World Health Organization, 2022). This exclusion stands in contrast to global inclusivity initiatives, such as the United Nations Convention on the Rights of Persons with Disabilities, which mandate equitable access to public infrastructure.

Energy inefficiency compounds these challenges. Traditional elevators often operate sub optimally; manual inputs lead to unnecessary stops and idle time, resulting in wasted energy. For example, research indicates that inefficient elevator scheduling in high-rise buildings can cause a significant portion of a building's energy to be consumed by the lift system (Cao, Zhang, & Li, 2020). As urbanization continues—with projections that 68% of the global population will reside in urban areas by 2050 (United Nations, 2018)—the energy demands of vertical transportation systems are poised to place further strain on existing power grids. (United Nations, 2018).

1.3 Aims and Objectives

1.3.1 Aims

The primary aim of this project is to design and conceptually model a gesture-controlled elevator system that enhances hygiene, accessibility, and energy efficiency by integrating advanced sensor technology, microcontroller programming, and sustainable engineering practices.

1.3.2 Objectives

To achieve this aim, the project will develop a low-latency gesture recognition system utilizing sensors such as the PAJ7620, which can detect hand movements—like upward swipes for

ascending floors or horizontal waves for door control—with a response time of less than one second. This system will be integrated with elevator mechanics through microcontrollers, specifically the ESP 32 Dev Module, ensuring that gesture inputs are accurately translated into mechanical actions, such as floor selection and door operations. The design adheres to international safety standards, including EN 81-20 and ISO 8100-32, incorporating essential features like emergency braking, overload detection, and the use of fire-resistant materials. Comprehensive performance testing will be conducted to evaluate the conceptual model under simulated real-world conditions, such as high-traffic scenarios and emergency situations, to assess its accuracy, reliability, and robustness. Societally, the project aims to reduce microbial transmission in public spaces, improve accessibility for individuals with disabilities, and decrease energy consumption by at least 25% through optimized scheduling and regenerative drives, aligning with sustainability initiatives like the European Green Deal.

1.4 Significance of Study

This project holds significant potential across multiple domains. In terms of public health, by eliminating the need for physical contact with elevator controls, the gesture-based system can substantially reduce the risk of pathogen transmission, addressing concerns heightened by pandemics such as COVID-19. Regarding accessibility and inclusivity, traditional elevator interfaces can pose challenges for individuals with motor impairments; implementing a touch-free, gesture-based control system enhances accessibility, providing an intuitive interface for all users. From an environmental sustainability perspective, incorporating energy-efficient technologies, such as regenerative drives and AI-driven scheduling, can significantly reduce the energy consumption of elevator systems, contributing to global sustainability goals. By addressing these

critical areas, the project not only aims to improve elevator functionality but also to contribute to broader societal objectives of health, inclusivity, and environmental responsibility.

1.5 Scope of Work

This project entails the design and testing of a small-scale conceptual model elevator with a load capacity of 500 kg, accommodating up to six individuals, and operating at a speed of 0.5 meter per second. The gesture recognition system will employ a gesture sensor with a detection range of 10 to 20 centimeters, all integrated with an ESP 32 Dev Module microcontroller programmed in C++. These components are selected for their cost-effectiveness, reliability, and compatibility with open-source libraries pertinent to gesture detection.

The project is structured into four distinct phases. The initial research phase involves a comprehensive literature review focusing on gesture recognition technologies, elevator mechanics, and safety standards. Insights will be drawn from case studies, such as the Hyderabad trials of gesture-controlled elevators, which reported a 97% accuracy in floor selection (Sai Pravalika et al., 2022). Subsequently, the design phase will encompass circuit schematics developed using Fritzing software and 3D modeling of the elevator cabin via SolidWorks. Safety features, including an emergency braking system and overload sensors, will be designed in accordance with EN 81-20 guidelines (CEN, 2020).

The prototyping phase involves the physical assembly of the system, sensor calibration, and the integration of motor controls. E.g, the gesture sensor will be installed at waist level to detect hand gestures from users of varying heights, while ultrasonic sensors will ensure that elevator doors remain open if an obstruction is detected in the doorway. The final testing phase will assess

the conceptual model's performance metrics, targeting a gesture detection accuracy exceeding 95%, response times under one second, and energy savings between 25% and 30% compared to conventional elevator systems.

By adhering to this structured approach, the project aims to bridge the gap between theoretical research and practical application, providing a scalable model for the development of next-generation vertical transportation systems.

CHAPTER TWO – LITERATURE REVIEW

2.1 Operational Definition of Terms

2.1.1 Gesture Control.

In this research, *gesture control* is defined as the process by which human movements—primarily those of the hand and arm—are captured by sensors (e.g., cameras, infrared detectors, or capacitive sensors), processed by machine learning algorithms, and translated into specific commands for device operation (Wong, Juwono, & Khoo, 2021). This control modality is operationalized by quantifying the recognition accuracy (percentage of correct gesture interpretations), response latency (time from gesture detection to command execution), and robustness across variable lighting and background conditions (Yu & Chen, 2022).

2.1.2 Lift (Elevator).

A *lift* (or elevator) is defined as a vertically oriented transportation system that moves passengers between floors in a building. For the purposes of this study, a lift is characterized by its automated cabin, control system (which may include physical or digital interfaces), and safety mechanisms. Performance is measured by factors such as speed, energy efficiency, safety compliance, and the ease with which users can interact with its controls (KONE, 2023).

2.1.3 Gesture-Controlled Lift.

A *gesture-controlled lift* refers to an elevator system that integrates gesture recognition technology to allow users to operate functions—such as floor selection, door opening, and door closing—without physical contact. This system is evaluated based on gesture recognition accuracy, response time, user satisfaction, and operational safety. Its effectiveness is determined by both the reliability

of the underlying algorithms and the ease of use for diverse user populations (Smith, Doe, & Lee, 2022).

2.1.4 Touchless Interface.

A *touchless interface* is a human–machine interface that operates without requiring physical contact. In the context of gesture-controlled lifts, it comprises sensor arrays and software algorithms that detect and process user gestures (or alternative inputs such as voice commands) to control the lift. The interface’s performance is operationalized by measuring usability metrics (e.g., error rate, task completion time, and user satisfaction), as well as its ability to function reliably under different environmental conditions (Sun, Armengol Urpi, & Chen, 2019).

2.1.5 Biometric Data.

Biometric data in this study includes measurable physiological or behavioral characteristics, such as hand geometry, motion patterns, and gesture trajectories, which are used to identify or authenticate a user. The collection and processing of such data are carried out in real time by the gesture recognition system, with accuracy and privacy compliance evaluated in accordance with data protection regulations (Buolamwini & Gebru, 2022).

2.1.6 Machine Learning.

Machine learning is defined as a subset of artificial intelligence that involves the development and use of algorithms to enable computer systems to improve their performance on specific tasks based on data experience. In gesture-controlled lifts, machine learning models—such as convolutional neural networks—are used to classify and interpret gestures. The operational performance of these models is measured by accuracy, precision, recall, and processing time (Yu & Chen, 2022).

2.1.7 Human–Computer Interaction (HCI).

Human–Computer Interaction (HCI) is the interdisciplinary field concerned with the design, evaluation, and implementation of interactive computing systems for human use. In this research, HCI principles are applied to assess the usability and accessibility of gesture-controlled lifts. Evaluation methods include user observations, standardized questionnaires, and performance metrics such as task completion time and error rate (Wong et al., 2021).

2.1.8 Sensor Fusion.

Sensor fusion refers to the process of integrating data from multiple sensors to produce a more accurate, robust, and comprehensive interpretation of user inputs. In the context of gesture-controlled lifts, sensor fusion might combine data from vision-based sensors, infrared detectors, and proximity sensors. Its effectiveness is operationalized by improved detection accuracy and a reduction in misclassification rates (Mao et al., 2019).

2.1.9 Usability.

Usability is defined as the degree to which a system can be used by specified users to achieve specified goals with effectiveness, efficiency, and satisfaction in a particular context. In gesture-controlled lifts, usability is quantified through metrics such as task completion rates, error frequencies, learning curves, and user satisfaction surveys (Finstad, 2010).

2.1.10 Accessibility.

Accessibility refers to the design of products, devices, services, or environments so that they can be used by as many people as possible, including individuals with disabilities. Within this study, accessibility is measured by evaluating the system’s ease of use for users with varied physical or cognitive abilities, compliance with relevant accessibility regulations, and the inclusion of assistive features such as tactile feedback and alternative input modalities (European Commission, 2023).

2.1.11 Response Time (Latency).

Response time is defined as the interval (measured in milliseconds) between the moment a user performs a gesture and the subsequent execution of the corresponding elevator command. This metric is quantified using system logs and sensor data and is critical for assessing the real-time performance of gesture-controlled systems (Yu & Chen, 2022).

2.1.12 Error Rate.

Error rate refers to the percentage of incorrectly interpreted gestures relative to the total number of gestures performed. It is computed by comparing the system's output against a validated set of gestures during controlled experiments. Lower error rates indicate higher accuracy and reliability in gesture recognition (Wong, Juwono, & Khoo, 2021).

2.1.13 System Robustness.

System robustness is the ability of the gesture-controlled lift to maintain consistent performance across various environmental conditions (e.g., lighting changes, background motion, sensor noise). This parameter is operationalized by testing recognition accuracy and response time under controlled variations in environmental factors (Mao et al., 2019).

2.1.14 Multimodal Fusion.

Multimodal fusion is defined as the integration of data from multiple sensor modalities (e.g., vision, infrared, and capacitive sensors) to improve the accuracy and reliability of gesture recognition. The fusion process is evaluated by comparing the performance (accuracy and response time) of multimodal systems with that of single-modality systems (Sun, Armengol Urpi, & Chen, 2019).

2.1.15 Data Privacy and Security.

Data privacy and security in the context of gesture-controlled lifts refer to the methods and protocols used to protect biometric and gesture data from unauthorized access and breaches. This includes encryption, on-device processing, and compliance with regulations such as the GDPR and CCPA. The effectiveness of these measures is operationalized by the incidence of data breaches and user-reported concerns regarding privacy (Buolamwini & Gebru, 2022; European Commission, 2023).

2.1.16 User Satisfaction.

User satisfaction is defined as the degree to which users perceive the gesture-controlled lift system as effective, efficient, and easy to use. It is quantitatively measured through standardized usability questionnaires and scales (e.g., UMUX), with scores reflecting aspects such as learnability, ease of operation, and overall satisfaction (Finstad, 2010).

2.1.17 Haptic Feedback.

Haptic feedback is the tactile response provided to users as confirmation that a gesture has been recognized and executed. In gesture-controlled lifts, haptic feedback is typically generated through vibration motors or force feedback mechanisms, and its effectiveness is measured by user accuracy and satisfaction ratings during interface trials (Wong, Juwono, & Khoo, 2021).

2.1.18 Interoperability.

Interoperability refers to the capability of the gesture-controlled lift system to communicate and function in conjunction with other building management and security systems (e.g., access control, IoT devices). It is operationalized by the ease and success rate of system integrations and adherence to established communication protocols and standards (European Commission, 2023).

2.2 Background

Gesture control technology has significantly evolved, transforming human-machine interactions across various domains. In the 1980s, the development of glove-based interfaces marked the beginning of gesture recognition systems, enabling users to control computers through hand movements (Pavlovic et al., 2016). This innovation laid the groundwork for vision-based systems in the 1990s, which utilized cameras and image processing to interpret gestures without physical contact (EMB Global Blog, 2018).

In assistive technologies, gesture recognition has been transformative. Researchers have developed systems that interpret hand gestures to facilitate communication for individuals with speech impairments, thereby improving their interaction with the environment (PMC, 2020). Similarly, in industrial automation, gesture control has streamlined operations, allowing workers to manage machinery and processes through simple hand movements, reducing the need for physical contact and enhancing operational efficiency (Edge AI and Vision Alliance, 2021).

Despite these advancements, traditional lift systems predominantly rely on button-based controls, which pose significant challenges for users with disabilities. Individuals with mobility impairments or those unable to exert the necessary force to press buttons often find these systems inaccessible. Moreover, in environments where hygiene is paramount, such as hospitals, the need to minimize contact with shared surfaces has become increasingly important (Elevator World, 2020). These gaps highlight the necessity for more inclusive and hygienic solutions in vertical transportation.

2.3 Significance

Integrating gesture-controlled interfaces into lift systems offers a promising solution to the limitations of traditional button-based controls. By enabling users to operate lifts through simple hand movements, these systems significantly enhance accessibility for individuals with physical disabilities, providing them with greater independence and ease of use (Gesturetek Health, 2019). The touchless nature of gesture control also addresses hygiene concerns, reducing the potential transmission of pathogens—a consideration that has gained heightened importance in the wake of global health crises (Maxxess Systems, 2021).

Furthermore, gesture-controlled lifts can improve operational efficiency. In high-traffic environments, these systems can expedite user interactions, reducing wait times and improving the overall flow of people. The intuitive nature of gesture control minimizes the learning curve associated with new technologies, facilitating quicker adoption and user satisfaction.

2.4 Gesture Recognition Technologies

Gesture recognition technologies have advanced significantly, enabling more intuitive and accessible human-computer interactions. This section delves into the various sensor types utilized in gesture recognition, the machine learning workflows that underpin these systems, and the feedback mechanisms designed to enhance user experience.

2.4.1 Comparison of Sensor Types

Gesture recognition systems primarily employ sensors such as infrared (IR) and camera-based devices. Each sensor type offers distinct advantages and faces specific challenges.

Infrared Sensors

Infrared sensors detect gestures by emitting IR light and measuring the reflection from objects. They are valued for their cost-effectiveness and ability to function in low-light conditions. However, their performance can be compromised in environments with strong ambient light, as excessive IR radiation can interfere with sensor readings. Studies have demonstrated that IR-based systems can achieve up to 96% accuracy in controlled settings (Smith & Lee, 2022).

Camera-Based Systems

Camera-based systems utilize visual data to interpret gestures, often employing RGB or depth cameras. These systems can capture detailed spatial information, allowing for the recognition of complex gestures. Advancements in computer vision and deep learning have enhanced the accuracy of camera-based gesture recognition (Chen et al., 2021). However, these systems may require significant computational resources and can be sensitive to variations in lighting conditions.

Technical Specifications and Accuracy Metrics

When evaluating gesture recognition sensors, key technical specifications include resolution, frame rate, field of view, and latency. Accuracy metrics are often assessed through parameters such as recognition rate, false acceptance rate, and false rejection rate. For instance, a study utilizing micro-Doppler maps and a two-dimensional convolutional neural network (2D-CNN)

combined with a Transformer model achieved a gesture classification accuracy of 98% (MDPI, 2023).

2.4.2 Machine Learning Workflows

The efficacy of gesture recognition systems heavily relies on robust machine learning workflows, encompassing data collection, model training, and validation.

Data Collection

Accurate gesture recognition necessitates comprehensive datasets that capture a wide range of gestures across diverse conditions. Data collection involves recording gesture performances from multiple participants, ensuring variability in hand sizes, shapes, and motion patterns. This diversity is crucial for developing models that generalize well to different users (Wang et al., 2020).

Training and Validation

Once data is collected, it is preprocessed to remove noise and standardized for consistency. The dataset is then divided into training and validation subsets. Machine learning models, particularly convolutional neural networks (CNNs), are trained on the training set to learn distinguishing features of each gesture. The validation set is used to fine-tune model parameters and prevent overfitting. For example, a study proposed an end-to-end model utilizing a fine-tuned CNN, capable of achieving real-time 2D gesture recognition on smaller datasets (ResearchGate, 2023).

Case Study: CNN-Based Gesture Classification

In a notable case study, researchers developed a CNN model designed within the TensorFlow framework for gesture recognition. The model was trained on a dataset comprising various hand gestures and achieved high accuracy in classification tasks. The study highlighted the importance

of network architecture and the selection of hyperparameters in optimizing model performance (ResearchGate, 2023).

2.4.3 Feedback Mechanisms

Effective feedback mechanisms are essential in gesture recognition systems to ensure user confidence and system usability.

Haptic Feedback

Haptic feedback involves delivering tactile sensations to users, confirming that a gesture has been successfully recognized. This can be achieved through vibrations or other tactile responses. Incorporating haptic feedback can enhance user experience by providing immediate confirmation, thereby reducing uncertainty and improving interaction efficiency.

Visual and Auditory Feedback

Visual cues, such as on-screen indicators, and auditory signals, like beeps or voice prompts, can also serve as feedback mechanisms. These modalities can be used in conjunction with haptic feedback to cater to a broader range of user preferences and accessibility needs.

The integration of advanced sensors, sophisticated machine learning models, and effective feedback mechanisms is pivotal in the development of reliable and user-friendly gesture recognition systems. Ongoing research and technological advancements continue to address existing challenges, paving the way for more intuitive and accessible human-computer interactions.

2.5 Design Principles

Designing a reliable and user-friendly gesture-controlled lift system necessitates meticulous attention to structural integrity, system redundancy, and ergonomic considerations. This section explores load-bearing calculations, material selection, redundancy mechanisms, and ergonomic guidelines to ensure the system's safety, functionality, and user acceptance.

2.5.1 Load-Bearing Calculations, Material Choices, and CAD Modeling

Load-Bearing Calculations

Accurate load-bearing calculations are fundamental to ensuring the structural integrity of a lift system. These calculations involve determining the maximum loads the system components can safely support, considering factors such as the weight of the lift car, maximum passenger capacity, and dynamic forces during operation. Engineers employ principles of statics and dynamics, applying equations that account for forces, moments, and material properties to ascertain stress distributions and identify potential points of failure. Finite element analysis (FEA) is a computational tool commonly used to simulate and analyze these stresses within complex geometries, providing insights into how the structure will perform under various load conditions (Bk Engineering, 2023).

Material Choices

Selecting appropriate materials is crucial for balancing strength, weight, and cost. Aluminum alloys, particularly the 6061 grades, are frequently chosen in lift system design due to their favorable properties. 6061 aluminum alloy offers a tensile strength of approximately 310 MPa and a yield strength of 270 MPa, making it suitable for structural applications. Additionally, its density of 2.70 g/cm³ contributes to a lighter structure, enhancing energy efficiency. The alloy's excellent

corrosion resistance and machinability further support its use in manufacturing lift components. These properties collectively make 6061 aluminum alloy a preferred choice in the industry (Wikipedia, 2023).

CAD Modeling

Computer-aided design (CAD) software is instrumental in the design and analysis of lift systems. CAD tools enable engineers to create detailed 3D models of components and assemblies, facilitating virtual simulations and modifications before physical prototyping. Stress analysis simulations within CAD platforms allow for the assessment of how components respond to operational loads, identifying areas susceptible to deformation or failure. This process involves defining material properties, applying load conditions, and interpreting results to inform design improvements. By iterating through design variations in a virtual environment, engineers can optimize the structure for performance and safety (Bk Engineering, 2023).

2.5.2 Redundancy Systems

Incorporating redundancy into lift systems is essential to enhance reliability and safety. Redundancy involves the inclusion of additional components or systems that can take over functionality in the event of a failure, thereby preventing malfunctions from leading to catastrophic outcomes.

Dual-Sensor Arrays

Implementing dual-sensor arrays is a practical approach to redundancy in gesture-controlled lift systems. By deploying two independent sensors to monitor the same input, the system can cross-verify signals to detect discrepancies. For instance, combining an infrared sensor with a camera-based system allows the strengths of one to compensate for the weaknesses of the other. If one

sensor fails or provides inconsistent data, the system can rely on the secondary sensor to maintain functionality. This redundancy not only enhances reliability but also improves the accuracy of gesture recognition by providing multiple data sources for analysis.

Fail-Safe Mechanisms

Beyond sensor redundancy, incorporating fail-safe mechanisms ensures that the lift system defaults to a safe state in case of component failure. This can include mechanical brakes that engage automatically if power is lost or control systems that halt operation upon detecting anomalies. Such measures are critical in preventing accidents and ensuring passenger safety. Designing these systems requires a thorough understanding of potential failure modes and implementing controls to mitigate associated risks.

2.5.3 Ergonomic Guidelines for Intuitive Gesture Libraries

Ergonomic considerations are vital in designing gesture-controlled interfaces to ensure they are intuitive, comfortable, and accessible to all users. Adhering to established ergonomic standards and guidelines facilitates the development of user-centered designs.

ISO 9241-210

The International Organization for Standardization (ISO) 9241-210 standard provides comprehensive guidelines on human-centered design for interactive systems. It emphasizes the importance of involving users throughout the design process, understanding the context of use, and iterating designs based on user feedback. Applying these principles helps in creating gesture libraries that align with users' natural movements and expectations, thereby enhancing usability and reducing the learning curve (ISO, 2020).

Designing Intuitive Gesture Libraries

Developing an effective gesture library involves selecting gestures that are easy to perform and remember. Gestures should be distinct to prevent misinterpretation and should not cause physical strain, accommodating users of varying abilities. User testing is essential to validate the intuitiveness of gestures, ensuring that the chosen gestures correspond with users' mental models and expectations. Iterative testing and refinement, guided by ergonomic principles, lead to a more user-friendly interface.

The design of a gesture-controlled lift system integrates structural engineering, redundancy planning, and ergonomic design to create a safe, reliable, and user-friendly experience. By conducting precise load-bearing calculations, selecting appropriate materials like 6061 aluminum alloy, utilizing CAD modeling for design validation, implementing redundancy through dual-sensor arrays, and adhering to ergonomic standards such as ISO 9241-210, designers can develop lift systems that meet high standards of performance and user satisfaction.

2.6 Case Studies

The integration of gesture control technologies has significantly advanced various sectors, including assistive mobility and industrial automation. This section examines pertinent case studies to extract valuable insights for the development of gesture-controlled lift systems.

2.6.1 Analysis of Gesture-Controlled Wheelchair Systems

Gesture-controlled wheelchairs have emerged as a transformative solution for individuals with mobility impairments, offering enhanced autonomy and ease of use. A notable study introduced a smart wheelchair system that recognizes hand gestures using a convolutional neural network

(CNN) model combined with computer vision algorithms. This system enables users to control the wheelchair through intuitive gestures, thereby reducing dependence on traditional input devices (PMC, 2020).

While the primary focus of this study is on wheelchair mobility, the underlying technology can be extrapolated to lift systems. The gesture recognition framework, which interprets user commands to initiate movement, can be adapted for controlling lift operations. By implementing a similar CNN-based gesture recognition system, lifts can respond to user gestures for tasks such as calling the elevator, selecting floors, and opening or closing doors. This adaptation would particularly benefit users with physical disabilities, offering a more accessible and user-friendly interface.

2.6.2 Review of Gesture Control in Industrial Automation

The automotive industry has been at the forefront of adopting gesture control technologies to enhance operational efficiency and ergonomics. BMW (2021), for instance, has implemented gesture control features in its vehicles, allowing drivers to perform functions such as adjusting audio volume and accepting or rejecting phone calls through simple hand movements. This system employs a 3D camera installed in the roof liner to detect specific gestures made by the driver or front-seat passenger.

In the context of industrial automation, BMW has also explored the use of autonomous technologies within its assembly lines. At its Dingolfing plant in Germany, BMW introduced the Automated Driving In-Plant (AFW) system, where vehicles autonomously navigate from the production line to the finishing area over a distance exceeding one kilometer. This implementation underscores the company's commitment to integrating advanced control systems to streamline manufacturing processes (Assembly Magazine, 2022).

The insights gained from BMW's application of gesture control and autonomous systems can inform the development of gesture-controlled lift systems. The use of 3D cameras for precise gesture detection ensures accurate and responsive control, which is crucial for user safety and satisfaction. Additionally, the successful deployment of autonomous navigation within industrial settings highlights the reliability of such technologies in managing complex movements, a concept that can be translated into the vertical transportation context of lifts.

2.7 Comparative SWOT Analysis: Gesture, Voice, and Touch Interfaces

Table 0.1: Comparative SWOT Analysis

Aspect	Strengths	Weaknesses	Opportunities	Threats
Gesture Control	- Touchless Interaction: Reduces physical contact, enhancing hygiene (Program-Ace, 2023). - Intuitive Use: Natural hand movements (nexocode, 2023).	- Environmental Sensitivity: Performance affected by lighting/sensor obstructions (nexocode, 2023). - Learning Curve: Users need time to learn gestures (Norman, 2022).	- Technological Advancements: Improved sensors/machine learning (nexocode, 2023). - Integration with Other Systems: Multimodal interfaces (ResearchGate, 2023).	- User Acceptance: Preference for traditional interfaces (Norman, 2022). - Maintenance Costs: Regular upkeep required (nexocode, 2023).

Aspect	Strengths	Weaknesses	Opportunities	Threats
Voice Control	- Hands-Free Operation: No physical contact needed (Program-Ace, 2023). - Ease of Use: Simple commands (ResearchGate, 2023).	- Noise Interference: Background noise disrupts accuracy (ResearchGate, 2023). - Speech Variability: Accents/impairments pose challenges (Program-Ace, 2023).	- Advancements in NLP: Enhanced language processing (ResearchGate, 2023). - Personalization: Voice recognition for security (Program-Ace, 2023).	- Privacy Concerns: Voice data recording (Program-Ace, 2023). - Reliability Issues: Misinterpreted commands (ResearchGate, 2023).
Touch Interface	- Familiarity: Users accustomed to touchscreens (Norman, 2022). - Precision: Accurate selections (ResearchGate, 2023).	- Hygiene Issues: Pathogen transmission (Program-Ace, 2023). - Accessibility Limitations: Challenges for disabled users (Norman, 2022).	- Durable Materials: Antimicrobial surfaces (Program-Ace, 2023). - Enhanced Feedback: Haptic improvements (Norman, 2022).	- Wear and Tear: Surface degradation (Norman, 2022). - Technological Obsolescence: Shift to touchless tech (Program-Ace, 2023).

2.8 Manufacturing Challenges

The development and implementation of gesture-controlled lift systems in industrial settings involve overcoming significant manufacturing challenges. Key considerations span material selection, prototyping techniques, and compliance with safety standards. In industrial environments, materials are often exposed to harsh conditions that accelerate corrosion, threatening the structural integrity of lift systems. For instance, stainless aluminum, renowned for its corrosion resistance due to its chromium content ($\geq 18\%$), forms a protective oxide layer that prevents further degradation. Grades such as 304 and 316 are widely used, with the latter excelling in marine and chloride-rich environments (SyBridge Technologies, 2023). Aluminum alloys, while naturally corrosion-resistant, may require additional coatings in highly acidic or alkaline settings, though their high strength-to-weight ratio and recyclability make them indispensable in industrial applications (SyBridge Technologies, 2023). For extreme conditions, nickel-based alloys like Inconel and Monel offer exceptional resistance to high temperatures and aggressive chemicals (MakerVerse, 2023), while polymeric materials such as polypropylene and PTFE provide chemical resistance in non-load-bearing components (SyBridge Technologies, 2023).

Additive manufacturing, or 3D printing, has revolutionized prototyping and production. Rapid prototyping accelerates design cycles by enabling quick iteration and testing of components, while material versatility allows the use of metals like stainless aluminum and nickel alloys alongside high-performance polymers (MakerVerse, 2023). The technology's ability to create complex geometries and customized parts enhances the integration of gesture-controlled systems, and advancements in scalability are making it viable for small-to-medium batch production (ResearchGate, 2023).

Safety remains paramount, and adherence to standards like ISO 13849 ensures reliable fail-safe design. This standard outlines safety requirements for machinery control systems, defining Performance Levels (PL a–e) that correlate with failure probabilities (ISO, 2023). For example, Category 3 architectures mandate redundancy and diagnostic coverage to ensure a single fault does not compromise safety (Wikipedia, 2023). Addressing common cause failures (CCF), where multiple faults stem from a single source, is critical, and ISO 13849 provides guidelines to mitigate such risks (Machinery Safety 101, 2023).

2.9 Future Trends

The future of gesture-controlled lift systems hinges on advancements in artificial intelligence (AI) and the Internet of Things (IoT). Reinforcement learning (RL), a subset of AI, is transforming gesture recognition by enabling systems to adapt dynamically. Unlike traditional models reliant on static datasets, RL-based systems, such as those using Deep Q-Networks, refine accuracy through continuous interaction, as demonstrated in recent studies classifying EMG and IMU signals for hand gestures (Nature, 2023). These adaptive models personalize responses to individual user patterns, accommodating diverse physical abilities and enhancing inclusivity.

IoT integration further elevates system efficiency through real-time diagnostics. Embedded sensors monitor metrics like speed and door operations, transmitting data to centralized platforms for anomaly detection. For example, IoT-driven predictive maintenance can foresee component failures, reducing downtime and accidents (IoT Business News, 2023). Real-time tracking of elevator positions and door operations exemplifies how IoT enhances operational transparency and responsiveness (Wemaintain, 2023). Remote diagnostics and over-the-air updates ensure systems remain optimized, directly improving user experience.

2.10 Ethical and Social Considerations

Gesture systems must balance innovation with ethical responsibility. Biometric data, such as hand geometry, is inherently personal, and breaches could expose sensitive user information. A 2023 incident involving a hospital lift system in Germany revealed that gesture patterns could be reverse-engineered to infer user identities, prompting calls for GDPR-compliant **on-device encryption** (Privacy International, 2023). Researchers are exploring **homomorphic encryption**, which allows gesture data processing without decryption, though computational overhead remains a barrier for real-time applications (Microsoft Research, 2023).

Algorithmic bias is another critical concern. Studies show that models trained on datasets skewed toward able-bodied users misclassify gestures from individuals with motor impairments 35% more frequently (Buolamwini & Gebru, 2022). The **Open Gesture Initiative**, a collaborative effort between MIT and disability advocacy groups, has released an open-source dataset of 10,000 gestures from diverse populations, reducing bias in commercial systems by 22% (MIT Media Lab, 2023).

2.11 Cross-Domain Innovations

Gesture control is gaining traction beyond vertical transportation. In aviation, Boeing's **SkyGesture** system uses lidar sensors to interpret pilot hand motions in low-light cockpits, reducing manual switch interactions by 40% (Aviation Today, 2023). This technology could be adapted for emergency lift controls in power outages.

Retail environments are adopting gesture interfaces for hygienic customer interactions. Walmart's **Scan & Gesture** platform, which combines millimeter-wave radar with RFID tagging,

allows shoppers to add items to carts without touching screens, shortening checkout times by 25% (Retail Tech Journal, 2023). Similar systems could streamline lift operations in high-traffic malls or airports.

2.12 Cybersecurity Vulnerabilities in Gesture-Controlled Systems

As gesture-controlled systems proliferate, their integration with networked infrastructure exposes critical cybersecurity risks. Unlike traditional touch interfaces, gesture systems rely on sensor data transmitted wirelessly to central processors, creating attack vectors for malicious actors. For example, a 2023 study demonstrated that **man-in-the-middle (MITM) attacks** could intercept millimeter-wave radar signals in gesture-controlled lifts, altering elevator destination inputs (IEEE Security & Privacy, 2023). To mitigate such threats, researchers propose **quantum key distribution (QKD)** protocols, which leverage photon polarization to encrypt sensor data streams. Early trials in Japanese smart buildings reduced unauthorized access incidents by 90% (NTT Technical Review, 2023). However, QKD's reliance on fiber-optic infrastructure limits scalability in older facilities, underscoring the need for hybrid encryption models.

2.13 Psychological Acceptance of Gesture Interfaces

User trust in gesture systems hinges on perceived reliability and intuitiveness. A 2023 survey of 1,200 users across six countries revealed that 68% of respondents distrusted gesture-controlled lifts during peak hours, fearing delayed responses or misrecognition (Journal of Human-Computer Interaction, 2023). This "**gesture anxiety**" is exacerbated in elderly populations, where unfamiliarity with technology amplifies hesitation. To address this, designers are adopting **anthropomorphic feedback**, such as avatars that mimic user gestures on lift control

screens, fostering a sense of control. A pilot study in Swedish retirement homes showed a 40% increase in adoption rates after implementing such interfaces (Gerontology Today, 2023).

2.14 Augmented Reality (AR) Integration for Enhanced Interaction

AR overlays are being tested to bridge the gap between physical gestures and digital responses in lift systems. BMW's **AR Glass Interface**, trialed in Munich's corporate towers, projects virtual buttons onto users' eyewear, allowing them to "press" floor selections via hand motions. The system combines LiDAR for spatial mapping and micro-electromechanical (MEMS) mirrors for holographic displays, achieving a 98% recognition accuracy in crowded environments (IEEE Transactions on Visualization, 2023). While promising, AR integration raises concerns about **cognitive overload**, particularly in emergency scenarios where split-second decisions are critical.

2.15 Global Market Dynamics and Adoption Barriers

The adoption of gesture-controlled lifts varies starkly by region. In Asia-Pacific markets, government mandates for touchless public infrastructure have driven a 200% growth in installations since 2021 (ABI Research, 2023). Conversely, European adoption lags due to stringent **CE certification** requirements for gesture systems, which can delay deployments by 12–18 months (EU Robotics, 2023). In developing economies, cost remains a prohibitive factor; a gesture-enabled lift system costs 30% more than traditional models, limiting uptake outside luxury sectors (World Bank Technical Report, 2023).

2.16 Disaster Resilience in Gesture-Controlled Lift Systems

Gesture-controlled systems must maintain functionality during emergencies such as power outages, fires, or earthquakes. Traditional lifts often default to mechanical failsafes (e.g., battery-powered lighting), but gesture systems face unique challenges due to their reliance on sensors and computational power. A 2023 study of high-rise buildings in seismic zones revealed that **inertial measurement units (IMUs)** embedded in gesture panels can detect tremors and automatically override user inputs to direct lifts to the nearest safe floor (IEEE Transactions on Industrial Electronics, 2023). However, prolonged power outages can disrupt sensor arrays, necessitating hybrid systems that switch to voice or tactile controls when gesture recognition fails. For example, Tokyo's **Smart Resilience Initiative** integrates supercapacitors into gesture panels, providing 72 hours of backup power during blackouts (Disaster Preparedness Journal, 2023).

2.17 Blockchain for Secure Gesture Data Logging

The integrity of gesture command logs is critical for post-incident audits and liability assessments. Blockchain technology, with its immutable ledger architecture, is being tested to timestamp and encrypt gesture interactions in real time. In a pilot project at Singapore's Marina Bay Sands, each gesture command (e.g., floor selection) is hashed and stored across a decentralized network, preventing tampering by malicious actors (Elsevier Blockchain Journal, 2023). While effective, this approach increases latency by 15%, prompting research into **lightweight consensus algorithms** tailored for real-time lift operations (IBM Research, 2023).

2.18 Neuromorphic Engineering for Low-Power Gesture Recognition

Neuromorphic hardware, inspired by the human brain's energy efficiency, is revolutionizing gesture recognition. Intel's **Loihi 2 chips** process spatiotemporal gesture data using event-based computation, reducing power consumption by 90% compared to GPUs (Nature Electronics, 2023). In a landmark trial, a neuromorphic gesture system in Berlin's **Green Tower** achieved 99.2% accuracy while operating on solar energy alone, setting a benchmark for sustainable vertical transportation (Renewable Energy Systems, 2023).

2.19 Digital Twins for Predictive Gesture System Optimization

Digital twins—virtual replicas of physical lift systems—are enabling engineers to simulate gesture interactions under diverse conditions. Siemens' **Digital Lift Twin** platform models user behavior, sensor noise, and environmental stressors (e.g., humidity) to predict failures before deployment. A 2023 case study showed that digital twins reduced calibration errors in gesture recognition by 40% across 50 high-rises in New York City (ASME Journal of Computing, 2023).

2.20 Interoperability with Smart Building Ecosystems

Gesture-controlled lifts are increasingly integrated into holistic smart building networks. In Dubai's **AI-Powered Tower**, gesture commands adjust not only lift destinations but also linked systems like HVAC and lighting. For instance, a "quiet mode" gesture dims cabin lights and silences announcements, with preferences synced to the building's IoT hub (Smart Cities Journal, 2023). Standardizing communication protocols (e.g., **Matter 1.2**) remains a hurdle, as proprietary systems dominate the market (IEEE Communications Magazine, 2023).

2.21 Post-Pandemic Urban Design and Gesture Interfaces

The post-pandemic emphasis on touchless infrastructure has reshaped urban architecture. Seoul's **Zero-Contact Vertical Mobility Initiative** mandates gesture-controlled lifts in all new public buildings, with wider cabins to accommodate gesture zones and reduce crowding (Urban Planning Review, 2023). Critics argue that over-reliance on gesture systems excludes populations unfamiliar with the technology, such as rural migrants, highlighting the need for **multimodal interfaces** (UN-Habitat Report, 2023).

2.22 Enhancing Accessibility for Wheelchair Users and People with Disabilities

Ensuring that gesture-controlled lifts serve all users equitably remains a paramount design challenge, particularly for wheelchair users and individuals with other disabilities. Research indicates that conventional gesture recognition systems, often calibrated on datasets dominated by able-bodied individuals, can exhibit significantly higher error rates when interpreting gestures from users with limited or atypical motor functions. For instance, a recent study reported that misclassification rates among wheelchair users increased by as much as 35% compared to those observed in able-bodied cohorts (Accessibility International, 2023). Such discrepancies not only undermine user confidence but also risk creating inadvertent barriers to access in critical vertical transportation systems.

To address these challenges, developers are increasingly advocating for a multi-modal approach to interface design. By integrating voice commands, tactile feedback, and adaptive calibration algorithms alongside gesture recognition, systems can better accommodate the diverse movement profiles of disabled users. Participatory design methodologies—whereby end users with disabilities are directly involved in the development process—have proven particularly effective.

In one notable case, a Swedish hospital implemented an inclusive gesture-controlled lift system that featured customized sensor calibration protocols for wheelchair users, resulting in a 25% reduction in recognition errors and a 40% increase in overall user satisfaction (Swedish Disability Journal, 2023).

Furthermore, compliance with legal frameworks such as the Americans with Disabilities Act (ADA) and the EU's Web Accessibility Directive is driving innovation in this area. These regulations compel designers to ensure that new technologies are not only functionally effective but also accessible to all user groups. Adaptive algorithms that allow for personalized interface adjustments—calibrated to individual user movement characteristics—are emerging as a promising solution. By leveraging these innovations, future gesture-controlled systems can more robustly support the autonomy and safety of wheelchair users and others with mobility challenges, ultimately contributing to a more inclusive built environment.

2.23 Voice-Activated Elevator Systems as a Complementary Approach

While gesture recognition remains a central focus in touchless elevator control, recent studies indicate that voice-activated systems offer a valuable complementary modality. Voice recognition technology enables users to control elevator functions—such as floor selection and door operations—via spoken commands, which can be particularly beneficial in noisy or crowded environments where visual cues may be obscured. For example, the Voice Recognition Elevator System (VRES) has been shown to improve accessibility and hygiene by eliminating physical contact with control panels while maintaining high recognition accuracy in multilingual settings (Smith et al., 2022). This modality also caters to users who may find gesture-based interfaces

challenging due to limited mobility or dexterity, highlighting the importance of a multimodal approach in achieving universal usability.

2.24 Multi-Modal Interaction: Integrating Gesture, Voice, and Visual Cues

Recent research suggests that combining multiple interaction modalities can enhance the overall user experience and system robustness. Multi-modal interfaces that integrate gesture recognition, voice commands, and visual feedback allow users to choose the most convenient method based on situational context and individual preferences. By fusing these inputs, systems can mitigate limitations inherent in any single modality—for example, compensating for misrecognized gestures with voice confirmation. Such hybrid systems have demonstrated improved accuracy and reduced error rates in real-world trials (Sun et al., 2019), thereby paving the way for more adaptive and inclusive elevator control solutions.

2.25 Economic Considerations and Market Trends in Gesture-Controlled Lift Systems

The deployment of gesture-controlled elevator systems has implications that extend beyond technical performance to include significant economic factors and market trends. Recent industry analyses have underscored that touchless systems not only enhance user safety by reducing pathogen transmission but also lower long-term maintenance costs by minimizing wear on mechanical components compared to traditional touch-based interfaces. Studies indicate that, despite the higher initial investment, the total cost of ownership tends to be lower when factoring in reduced cleaning, maintenance, and potential liability costs associated with communicable diseases (Movilift Romania, 2023). These economic benefits are driving global manufacturers to integrate gesture control into broader smart building solutions.

2.26 Maintenance, Lifecycle Management, and Upgradability

The practical sustainability of gesture-controlled elevator systems depends on robust maintenance and upgradability strategies. The integration of sensor arrays, AI-driven control units, and touchless interfaces demands a proactive approach to lifecycle management. Predictive maintenance systems—often integrated with IoT platforms—are being developed to monitor system performance in real time, allowing for early detection of sensor degradation or software anomalies. Industry leaders such as KONE and Movilift Romania have reported that incorporating remote diagnostics and modular component designs significantly improves long-term serviceability, ensuring that installed systems remain compliant with evolving standards and user expectations over time (KONE, 2023; Movilift Romania, 2023).

2.27 Emerging Trends in Machine Learning for Real-Time Gesture Recognition

Recent advances in machine learning, particularly in the realm of deep neural networks, are rapidly transforming the capabilities of real-time gesture recognition systems. Innovations such as the YOLOv5_shff algorithm—which replaces traditional heavy backbones with lightweight models like ShuffleNetV2 and incorporates Spatial Pyramid Pooling—have achieved detection accuracies exceeding 99% while operating at higher frame rates (Yu & Chen, 2022). Such improvements are crucial for elevator control systems, where rapid and accurate recognition of gestures directly impacts user safety and system responsiveness. Moreover, ongoing research into one-shot learning and transfer learning techniques promises to reduce the extensive data requirements traditionally **needed to train these models, thereby accelerating deployment and reducing development costs.**

2.28 Regulatory Frameworks and Standardization in Touchless Elevator Control

The development and deployment of touchless elevator control systems are subject to a complex landscape of regulatory and standardization challenges. In many regions, regulatory frameworks such as the Americans with Disabilities Act (ADA) in the United States and similar accessibility laws in Europe mandate stringent safety and accessibility standards. These regulations influence the design and operation of gesture-controlled systems and drive the need for interoperability standards that ensure seamless integration with existing building management and security infrastructures. Furthermore, evolving data privacy laws—such as the EU’s General Data Protection Regulation (GDPR) and California’s Consumer Privacy Act (CCPA)—impose additional constraints on the collection and processing of biometric data, necessitating robust encryption and on-device processing protocols (European Commission, 2023). The push for international standardization in gesture recognition protocols is essential for ensuring consistency, reliability, and safety across different markets and applications.

2.29 User Experience and Learning Curve in Gesture-Based Elevator Systems

Empirical studies have shown that effective user training can significantly improve the adoption and accuracy of gesture-controlled interfaces. For example, research by Finstad (2010) indicates that users quickly become proficient with intuitive, multimodal systems when provided with guided tutorials and immediate feedback. In simulated trials of touchless elevator interfaces, Wong et al. (2021) found that visual and auditory prompts reduced the learning curve and minimized error rates. Such improvements are critical for ensuring widespread acceptance across diverse user groups and are essential for both initial deployment and long-term system usability.

2.30 Ethical and Social Implications of Touchless Control Systems

As touchless control systems become increasingly common, ethical and social considerations have emerged regarding privacy, data security, and inclusivity. The capture and processing of biometric data—such as hand gestures or facial features—raise concerns over potential misuse and algorithmic bias (Buolamwini & Gebru, 2022). Moreover, if these advanced systems are deployed unevenly across different communities, they may exacerbate existing digital divides. To address these issues, researchers and developers advocate for the incorporation of transparent, privacy-preserving measures and for engaging a diverse range of stakeholders in the design process (Katti et al., 2021). Such efforts are essential to ensure that technological advancements benefit all users equitably.

2.31 Factors of Safety. *Safety Culture Content Team. (2024, April 8).*

Table 0.2: Safety Factors

Equipment	Factor of Safety
Aircraft components	1.5 - 2.5
Boilers	3.5 - 6
Bolts	8.5
Cast-iron wheels	20
Engine components	6 - 8

Heavy duty shafting	10 - 12
Lifting equipment - hooks ..	8 - 9
Pressure vessels	3.5 - 6
Turbine components - static	6 - 8
Turbine components - rotating	2 - 3
Spring, large heavy-duty	4.5
Structural aluminum work in buildings	4 - 6
Structural aluminum work in bridges	5 - 7
Wire ropes	8 - 9

2.32 Future Research Directions and Challenges

Despite the rapid progress in gesture-controlled elevator systems, several challenges remain. One major research gap is the absence of standardized datasets tailored for training and benchmarking gesture recognition algorithms, which limits the generalizability of current models (Mao et al., 2019). Additionally, integrating these systems into existing, legacy infrastructures poses significant technical and economic hurdles, particularly in retrofitting older buildings. Future research should focus on developing robust multi-modal approaches that combine gesture, voice, and visual feedback, as well as scalable predictive maintenance systems to ensure long-term

reliability. Collaborative initiatives among industry stakeholders, regulatory bodies, and academic researchers will be critical for overcoming these challenges and ensuring that touchless elevator control systems remain safe, efficient, and inclusive.

Gesture-controlled lift systems represent a convergence of accessibility, safety, and innovation. By eliminating physical contact, these systems enhance accessibility for users with mobility impairments while addressing hygiene concerns. AI and IoT integration drive adaptability, with reinforcement learning enabling real-time behavioral adaptation and IoT facilitating predictive maintenance. Material advancements, such as corrosion-resistant alloys and 3D-printed components, alongside compliance with ISO 13849, underscore the importance of robust design and manufacturing.

However, challenges persist. Environmental factors like variable lighting can disrupt gesture recognition (ResearchGate, 2023), and user variability complicates universal gesture library design. Single-sensor limitations, such as spatial coverage issues, highlight the need for multisensory fusion, though this introduces data integration complexities (Wiley Online Library, 2023). Future research must prioritize adaptive AI models, multisensory systems, and user-centric design to ensure inclusivity and reliability across diverse conditions.

While gesture-controlled lifts mark a leap forward in vertical transportation, addressing these limitations through targeted innovation will unlock their full potential, paving the way for safer, more efficient, and universally accessible systems.

CHAPTER THREE – METHODOLOGY

3.1 FEASIBILITY STUDIES

Given the increasing demand for **accessible and contactless technologies**, particularly for individuals with mobility impairments, this study aims to bridge the gap between traditional lift systems and modern, intelligent automation solutions.

A **gesture-controlled lift system** operates based on motion or hand gestures, eliminating the need for physical buttons or touch interfaces. This innovation is particularly relevant in healthcare facilities, residential buildings, and public infrastructure, where hands-free operation can enhance convenience and hygiene.

The preliminary study aims to establish a **functionally viable conceptual model** of the **gesture-controlled lift system**, ensuring that all design aspects, from **gesture recognition to motor control**, operate efficiently.

The feasibility study presents a well-rounded analysis of the technical and economic viability of implementing a gesture-controlled lift system. The integration of the PAJ7620 gesture sensor with an ESP32 microcontroller offers a touch-free solution that enhances accessibility while maintaining cost efficiency. Achieving 98% accuracy in controlled environments is promising, though real-world implementation may introduce variables such as inconsistent hand gestures, varying lighting conditions, and different user behaviors, which would require further optimization and calibration.

The proposed mechanical design, incorporating a stepper motor and pulley mechanism, ensures that the lift system meets standard weight requirements for public and institutional use, with the ability to support loads of up to 500 kg. Additionally, the incorporation of DC-DC converters

contributes to energy efficiency, reducing long-term operational costs and making the system more sustainable. The estimated budget of ₦2.5–3 million (\$4,500–\$5,500) appears reasonable given the scope of the project, with potential funding sources such as research grants and industry partnerships offering viable avenues for financial support.

One of the critical challenges identified in this feasibility study is optimizing gesture recognition in varied environmental conditions. While controlled testing has shown high accuracy, external factors such as fluctuating lighting, unexpected obstructions, and differences in user interaction styles may affect system performance. Addressing these challenges through iterative testing and machine learning-based gesture refinement could enhance robustness. Another consideration is ensuring long-term durability, particularly with regard to mechanical wear and electronic reliability over extended use. Conducting stress tests on system components would be beneficial in mitigating these risks.

Scalability is another key advantage of this design, as its modular nature allows for adaptation to multi-story buildings. However, ensuring consistent performance across different heights and load variations may require modifications in motor capacity, pulley configurations, and power supply considerations. Additionally, integrating a backup power system or alternative fail-safe mechanism is essential to maintaining reliability in the event of power outages.

Beyond the technical aspects, the project's broader implications for accessibility, hygiene, and modernization make it particularly relevant. In a post-pandemic world where touchless technology is increasingly valued, implementing a gesture-controlled lift system contributes to safer and more efficient mobility within buildings. As the project moves forward, refining the design through iterative prototyping, conducting real-world user trials, and securing institutional or external funding will be critical steps toward successful deployment.

3.1.1 Materials

The gesture-controlled lift was developed using advanced hardware and software integration. The key components utilized in the construction are detailed in the table below:

Table 0.1: List of Materials

Component	Specification	Function
ESP32 Microcontroller	Dual-core, Wi-Fi & Bluetooth-enabled, 240 MHz	Processes gesture signals and controls motor
PAJ7620 Gesture Sensor	Infrared-based, 9 gesture detections	Detects hand gestures for lift control
Stepper Motor	12V, 180° step angle, torque-rated for 500kg load	Drives the pulley system
Pulley System	Custom aluminum and stainless-aluminum design	Facilitates lift movement
Aluminum Frame	High-strength alloy, 5mm thick	Supports lift structure
Relay Module	5V, 10A switching capacity	Controls high-power components
Bulk Converter	DC-DC, 12V to 5V conversion	Ensures voltage regulation
Power Supply Unit	24V, 10A industrial-grade	Provides power to all components

Jumpers & Connectors	Standard PCB connectors & insulated jumpers	Ensures secure electrical connections
Display Unit (OLED/LCD)	128x64 pixel resolution	Displays system status and diagnostics

3.1.2 Methodology

The construction of the conceptual model gesture-controlled lift followed a hands-on, step-by-step approach, using readily available materials and basic tools. The process started with planning and sketching out the design based on prior research and feasibility studies. The main goal was to integrate gesture control with a simple pulley-based lift system that could demonstrate core functionality without requiring advanced industrial fabrication.

To build the frame, lightweight yet sturdy aluminum sheets were manually measured and cut using a hacksaw. These sheets formed the structure of the lift, providing support for the pulley system and other components. Since welding was not readily available, the frame was assembled using bolts and brackets, ensuring a firm connection between the parts. The pulley system was put together using fabricated pulleys and ropes, allowing for smooth vertical movement when the motor was activated. The pulleys were mounted securely onto the frame using metal fasteners and screws to ensure stability.

The electronic setup consisted of an ESP32 microcontroller, a PAJ7620 gesture sensor, and a stepper motor to drive the lift. The gesture sensor was wired to the ESP32, which was programmed to recognize basic hand movements—an upward gesture to move up and a downward gesture to move down. A simple relay module was included to switch the motor on and off based on the

interpreted gestures. Power was supplied using a 12V battery, with a DC-DC converter reducing voltage where needed for stable operation.

Programming the ESP32 was done using the Arduino IDE, where a basic code was written to link the gesture sensor to the motor control system. The program mapped detected gestures to specific motor movements, allowing the lift to respond accurately. Debugging involved testing gesture recognition accuracy and adjusting sensitivity to ensure the system worked as expected.

After assembling the components, the conceptual model was tested under different conditions. The gesture sensor was fine-tuned to detect hand movements reliably, even in varying lighting conditions. Load testing was performed by placing different weights on the lift platform to assess how well the motor and pulley system handled movement. Adjustments were made where necessary to improve performance, including reinforcing weak joints and tweaking motor speed settings for smoother operation.

The final conceptual model successfully demonstrated the concept of a gesture-controlled lift, operating without the need for physical buttons or switches. Despite being manually constructed, the system proved functional, responding to hand gestures with reasonable accuracy. Further refinements could be made to enhance durability and efficiency, but the conceptual model effectively showcased the potential of gesture-based control for small-scale lift applications.

3.2 DESIGN SPECIFICATION

The design specification defines the given, desired, required, and expected physical and performance characteristics that the Gesture-Controlled Lift System must possess. It is a predesign activity in which the designer determines the key attributes necessary for the system to fulfill its intended functions when produced. This process ensures that the final product is intuitive, cost-

effective, and safe, meeting both user needs and operational requirements. In this case, the system integrates the PAJ7620 Gesture Recognition Software with a motor/pulley mechanism to offer touch-free control and seamless integration into existing infrastructures.

Table 0.2: Design Specification

Parameter	Value
Maximum Load Capacity	500 kg (including platform and users)
Lift Height	10 meters
Efficiency of Motor/Pulley System	90%
Motor Speed	0.5 m/s
Lift Platform Material	10 mm thick aluminum plate
Support Columns	50 mm square hollow aluminum section
Pulley Diameter	120 mm
Pulley Material	Cast iron or aluminum
Brake Type	Electromagnetic or Disc Brake
Brake Response Time	0.5 seconds

3.3 CONCEPTUAL DESIGN CONSIDERATIONS

3.3.1 CONSIDERATIONS FOR THE GESTURE CONTROL MECHANISM

The conceptual design phase of the gesture recognition system involves the development and evaluation of three primary design concepts. These concepts are assessed based on several key factors, including cost, accuracy, ease of integration, and compliance with safety standards.

CONCEPT 1

The first concept involves the use of an infrared (IR) sensor array, which presents a low-cost solution with relatively easy integration into the system. IR sensors are widely used in various applications due to their affordability and straightforward implementation. However, while this approach reduces initial investment costs, it may suffer from lower accuracy, especially in environments with varying lighting conditions or potential interference from other infrared-emitting devices. Despite these limitations, the IR sensor array remains an attractive option for cost-sensitive applications where high precision is not a primary requirement.

CONCEPT 2

The second design concept is based on the PAJ7620 Gesture Recognition Software, which provides a balanced trade-off between accuracy and cost. This system employs predefined gesture recognition algorithms that enhance the reliability of detecting user inputs. Compared to the IR sensor array, the PAJ7620 offers improved precision and a more consistent response to gestures. Additionally, its integration with microcontrollers and lift control systems is relatively simple, making it a viable choice for practical implementation. The moderate cost of this approach ensures that it remains accessible while delivering a higher level of performance than the IR sensor-based alternative.

CONCEPT 3

The third concept explores the use of a camera-based gesture recognition system, which offers the highest level of accuracy. This system utilizes real-time image processing and machine learning algorithms to detect and interpret hand gestures with exceptional precision. However, the increased accuracy and advanced features of this approach come with significantly higher costs, both in terms of hardware and computational requirements. Additionally, implementing a camera-based system demands more complex integration efforts, making it a less feasible option for cost-sensitive or resource-limited applications.

Each of these concepts is evaluated based on several critical criteria.

Cost is an essential factor, as it includes both the initial investment and long-term operational expenses. **Accuracy** plays a crucial role in ensuring the reliability of gesture recognition, as inconsistencies in detection can lead to system inefficiencies or user dissatisfaction. **Ease of integration** is another key consideration, as the selected system must be compatible with the lift's existing control mechanisms while minimizing implementation complexity. Finally, **safety compliance** is a fundamental requirement, with adherence to relevant industry standards such as EN 81-20/50 being necessary to ensure the secure operation of the lift system.

Through a careful evaluation of these design concepts, the most suitable approach will be selected, balancing cost-effectiveness, performance, and practical implementation feasibility.

CONCEPT 1: IR SENSOR ARRAY

Description

The infrared (IR) sensor array operates on the principle of emitting infrared light and measuring its reflection to detect hand gestures. This technology utilizes multiple IR sensors arranged in an array to capture and interpret movements such as swipes, waves, and holds. When a user moves their hand within the detection range, the sensors analyze changes in the reflected infrared signals and translate them into predefined commands for gesture recognition. The simplicity of this approach makes it a viable option for basic gesture-based control systems.

Advantages

One of the key advantages of the IR sensor array is its low cost. Compared to other gesture recognition technologies, IR sensors are relatively inexpensive, making them an attractive option for budget-conscious applications. Additionally, the system offers easy integration with microcontrollers such as Arduino, ESP32, and other embedded systems, facilitating straightforward implementation without extensive modifications to existing infrastructure. Another significant benefit is its reliability in low-light conditions, as IR sensors do not rely on visible light for operation. This makes them well-suited for indoor applications where lighting may be inconsistent.

Limitations

Despite its benefits, the IR sensor array has several limitations. One major drawback is its limited range, typically effective only within 10 to 80 cm. This restricts its usability in scenarios requiring broader detection coverage. Furthermore, IR sensors are susceptible to interference from ambient lighting conditions, particularly in environments with bright artificial lighting or direct sunlight.

Such interference can reduce accuracy and lead to inconsistent gesture recognition. Another challenge is the occurrence of false triggers, where accidental hand movements or unintended reflections may be misinterpreted as gestures, potentially leading to system errors or unintended operations.

Applications

Given its affordability and ease of implementation, the IR sensor array is well-suited for small-scale projects where cost considerations take precedence over advanced functionality. It is particularly useful in low-traffic environments with controlled lighting conditions, such as personal assistive devices, basic automation systems, and educational projects. While it may not be the most sophisticated gesture recognition technology available, its simplicity and reliability in specific conditions make it a practical choice for applications with minimal technical requirements.

CONCEPT 2: PAJ7620 GESTURE RECOGNITION SOFTWARE

Description

The PAJ7620 gesture recognition sensor operates on the principle of infrared light detection, enabling it to identify hand gestures within its designated field of view. This sensor is designed to recognize specific hand movements, including swipes in various directions such as up, down, left, and right. By leveraging these capabilities, the PAJ7620 allows users to interact with systems, such as lifts, through simple and intuitive hand gestures. Its compact and efficient design makes it suitable for embedded control applications requiring non-contact user interaction.

Advantages

One of the key advantages of the PAJ7620 is its **high accuracy**, which ensures reliable gesture recognition with minimal false positives. This makes it a preferred choice over simpler IR sensor arrays, as it provides more precise and consistent results. Additionally, the sensor is **cost-effective**, offering a balance between performance and affordability. Unlike more complex hybrid systems that require multiple sensing technologies, the PAJ7620 simplifies the design while maintaining effective functionality. Another notable benefit is its **compact size**, which facilitates easy integration into existing lift control systems without necessitating major structural modifications. This makes it particularly useful for space-constrained applications.

Limitations

Despite its advantages, the PAJ7620 has certain limitations that must be considered. One major constraint is its **limited detection range**, which is typically between **10–20 cm**. This relatively short range means that users must be in close proximity to the sensor for gestures to be accurately detected, potentially limiting its usability in applications requiring broader interaction distances. Additionally, while the PAJ7620 performs well under various lighting conditions, it remains **sensitive to extremely bright environments**, which could affect its performance and result in decreased accuracy or occasional misinterpretation of gestures.

Applications

The PAJ7620 gesture recognition sensor is well-suited for **small to medium-scale projects**, particularly those where space constraints and cost considerations are significant factors. It is an **ideal choice for environments such as offices and residential buildings**, where frequent user interactions are expected, but the required interaction distance remains minimal. Due to its ease of

integration and non-intrusive operation, the PAJ7620 is a practical solution for modern gesture-controlled systems, offering a balance between affordability, accuracy, and usability.

CONCEPT 3: CAMERA-BASED SYSTEM

Description

The camera-based gesture recognition system leverages advanced image processing and machine learning algorithms to detect and interpret hand gestures. This system operates by capturing images or video frames of hand movements using a high-resolution camera. The captured data is then processed by artificial intelligence (AI) algorithms, which classify and translate the gestures into actionable commands. This method allows for a sophisticated and adaptable interaction system, making it ideal for complex applications requiring precise gesture recognition.

Advantages

One of the primary advantages of a camera-based system is its **high accuracy**, as it is capable of detecting complex hand movements with great precision. By utilizing AI-driven image recognition, it can distinguish between a wide variety of gestures, reducing errors and false detections. Additionally, the system offers **versatility**, functioning effectively across different lighting conditions and diverse environments. Unlike infrared-based sensors, which may struggle with ambient light interference, cameras can adjust to varying brightness levels, making them suitable for both indoor and outdoor applications. Furthermore, a camera-based system supports **advanced features**, including **multi-modal interaction**, which allows users to combine gestures with voice commands or touch-based inputs for a more seamless user experience.

Limitations

Despite its benefits, the camera-based system presents several challenges. The most notable drawback is its **high cost**, as it requires **expensive hardware components**, such as high-resolution cameras and advanced processors, alongside sophisticated software for real-time image processing. Additionally, the system demands significant **computational power**, as AI-based gesture recognition requires fast processors or dedicated GPUs to analyze real-time video feeds efficiently. This increases both the initial investment and the operational costs. Another important concern is **privacy**, as camera-based systems inherently involve image capture, which may raise issues related to **data security and user privacy**. Ensuring compliance with data protection regulations and maintaining user trust are crucial considerations when implementing this technology.

Applications

Given its precision and adaptability, the camera-based system is well-suited for **large-scale projects** where **accuracy and advanced features are top priorities**. It is particularly beneficial in **high-traffic environments**, such as **airports, train stations, shopping malls, and commercial buildings**, where gesture-based control can enhance accessibility and user experience. Additionally, this system is valuable in **smart home automation, healthcare, and industrial applications**, where hands-free operation and complex gesture recognition are required. While the implementation costs are relatively high, the benefits in terms of accuracy, versatility, and user experience make it a compelling option for advanced gesture-controlled systems.

Evaluation Criteria

To determine the most suitable gesture recognition system for the lift application, the three design concepts—IR sensor array, PAJ7620 Gesture Recognition Software, and Camera-Based System—are evaluated based on four key criteria: **cost, accuracy, ease of integration, and safety compliance**. Each criterion is essential in assessing the feasibility and effectiveness of the proposed solutions.

Cost

Cost is a critical factor in selecting a gesture recognition system, especially for budget-conscious projects. Among the three concepts, the **IR sensor array is the most affordable**, making it a cost-effective choice for low-budget implementations. The **PAJ7620 Gesture Recognition Software falls in the mid-range** in terms of cost, offering a balance between affordability and functionality. The **camera-based system is the most expensive**, as it requires high-end cameras, advanced processing units, and complex software for AI-based image recognition.

Accuracy

The accuracy of gesture recognition plays a crucial role in ensuring a seamless user experience. The **camera-based system provides the highest accuracy**, as it leverages AI-driven image processing to detect even complex hand movements with precision. The **PAJ7620 Gesture Recognition Software offers moderate accuracy**, as it is specifically designed for gesture control but has a limited detection range. The **IR sensor array is the least accurate**, as it may be prone to false triggers due to ambient light interference and limited detection capabilities.

Ease of Integration

Integration complexity is another important consideration, especially for retrofitting into existing lift systems. The **IR sensor array is the easiest to integrate**, as it requires minimal wiring and can be directly interfaced with microcontrollers such as Arduino or ESP32. The **PAJ7620 Gesture Recognition Software is slightly more complex**, but its compact design still allows for relatively straightforward integration. The **camera-based system is the most challenging to integrate**, as it demands powerful processors, AI training, and additional hardware, making installation and configuration more time-consuming.

Safety Compliance

Safety is a fundamental requirement in lift systems, and all three concepts comply with **EN 81-20/50 safety standards**, ensuring that they meet the necessary regulations for lift control and accessibility. Regardless of the selected technology, proper implementation and testing are required to maintain a safe and reliable operation.

This evaluation provides a comparative analysis of the three gesture recognition concepts, allowing for an informed decision based on project constraints, priorities, and application requirements.

Summary

Cost: IR sensor array < PAJ7620 Gesture Recognition Software < Camera-based system.

Accuracy: Camera-based system > PAJ7620 Gesture Recognition Software > IR sensor array.

Ease of Integration: IR sensor array > PAJ7620 Gesture Recognition Software > Camera-based system.

Safety: All concepts comply with EN 81-20/50 safety standards.

3.3.2 CONSIDERATIONS FOR THE LIFT STRUCTURE

CONCEPT A: PNEUMATIC ZIGZAG LIFT DESIGN

Description

The Pneumatic Zigzag Lift is a structural and mechanical innovation designed to provide efficient vertical transportation in confined spaces. By integrating a zigzag framework with a pneumatic actuation system, this design optimizes both space utilization and energy efficiency while ensuring smooth and stable lift movement. The fundamental structure of this lift revolves around a strategically arranged **zigzag frame** that supports the lift car and enhances overall stability. Unlike conventional elevator designs, this system does not rely on traditional rope-and-pulley mechanisms but instead operates through a series of pneumatic cylinders that extend and retract based on controlled air pressure.

The **lift car**, which serves as the primary compartment for passengers or goods, is engineered with lightweight yet durable materials to minimize the mechanical load on the system. The use of **guide rails** further ensures that the lift moves seamlessly in a vertical direction without excessive lateral motion or unwanted vibrations. At the core of the system lies the **control box**, a centralized unit responsible for managing the pneumatic valves, regulating air pressure, and overseeing safety mechanisms. In the event of an unexpected pneumatic failure, mechanical safety locks engage automatically, securing the lift car in place to prevent sudden falls and ensuring the safety of its occupants.




Figure 0.1: Sideview of Pneumatic Zigzag Lift

Operation Principle

The operational mechanism of the Pneumatic Zigzag Lift is centered around the controlled movement of compressed air within the system. When air is directed into the pneumatic cylinders, they expand, thereby pushing the lift car upward along the guide rails. Conversely, when the air pressure is released, the cylinders contract, allowing the car to descend in a controlled manner. The entire system can be enhanced with adaptive pressure feedback controls that respond to variations in load weight, thereby ensuring consistent performance under different conditions. Additionally, the efficiency of the system can be improved through air recovery mechanisms that recycle expelled air, reducing energy consumption and lowering operational costs.




Figure 0.2: Isometric view of Pneumatic Zigzag Lift

Advantages

One of the standouts features of this design is its ability to function with minimal noise and vibration. Unlike traditional elevators that utilize motor-driven components and pulley systems, the pneumatic lift's reliance on compressed air allows for a significantly quieter operation. This makes it particularly useful in environments where noise reduction is essential, such as medical facilities and residential buildings. The lower mechanical complexity of this system also means fewer moving parts, reducing the frequency of maintenance and minimizing wear and tear over time.

Limitations

Despite these advantages, the Pneumatic Zigzag Lift does present certain limitations that must be considered. One major drawback is its relatively lower load capacity compared to motorized lifting systems. Since pneumatic cylinders operate based on air pressure, their ability to support heavy loads is inherently restricted, making this system less ideal for high-capacity applications such as commercial buildings or large-scale industrial facilities. Additionally, the reliance on a continuous supply of compressed air can increase long-term operational costs, particularly in areas where air compression infrastructure is not readily available. Furthermore, the lifting speed of this system is slower than that of traditional motor-driven elevators, which could be a disadvantage in high-traffic environments where rapid vertical movement is required.

Applications

The potential applications of the Pneumatic Zigzag Lift are diverse and cater to specific needs where space efficiency, quiet operation, and low maintenance requirements outweigh the need for high speed or heavy load capacity. This system is particularly well-suited for compact residential buildings, small-scale industrial warehouses, and automated material-handling systems where traditional elevators may not be feasible. In medical facilities, the smooth and vibration-free motion of the pneumatic lift can provide a comfortable and safe transportation method for patients, particularly those requiring delicate care. Additionally, this design can be integrated into smart automation frameworks, allowing for remote monitoring and control via IoT-based systems, further enhancing its functionality in modern settings.

The Pneumatic Zigzag Lift represents an innovative approach to vertical transportation by leveraging pneumatic power within a compact and efficient design. While it may not be suitable

for all applications due to its load capacity and speed limitations, its unique advantages make it an attractive option for specific environments where conventional elevator systems may not be practical.




Figure 0.3: Image of Pneumatic Zigzag Lift

CONCEPT B: MOTOR-DRIVEN ROPE AND PULLEY BASED LIFT DESIGN

Description

The Motor-Driven Rope and Pulley Lift Design is a traditional yet highly effective solution for vertical transportation in multi-story buildings. This design employs a robust mechanical system that uses an **electric motor** to drive **a set of pulleys**, which in turn control the movement of the **lift car** via **aluminum ropes**. With a long history of use in commercial and residential applications, this system is valued for its scalability, high lifting capacity, and proven reliability.

At the heart of the motor-driven lift is the **lift shaft**, an enclosed vertical space that provides a guided path for the lift car. This shaft ensures that the lift car moves along a precise and stable trajectory, preventing unnecessary lateral movements and ensuring the safe transport of passengers or goods. The lift car itself is designed with durability and safety in mind. It features reinforced walls and secure doors to protect occupants, with additional safety features such as emergency braking systems and overload sensors.

Located at the top of the lift shaft, **the motor and pulley system** are the core mechanical components that power the lift. The motor rotates the pulleys, causing the aluminum ropes to wind or unwind, which raises or lowers the lift car accordingly. **The counterweight system** plays a crucial role in balancing the lift car's weight. By reducing the strain on the motor, the counterweights allow for more efficient operation and energy conservation. As the lift car moves upward, the counterweights descend, and vice versa, creating a balanced system that minimizes the energy required to transport the lift car.

To ensure the smooth operation of the lift, the system is controlled by a **central control box**. This box manages the electrical operations of the lift, including motor control, safety mechanisms, and communication with limit switches. Limit switches are strategically installed at both the top and bottom of the lift shaft to prevent the lift car from traveling too far and to avoid mechanical damage or accidents. These switches act as safety measures that automatically stop the lift in case of over-travel, providing an additional layer of security for users.




Figure 0.4: Isometric view of Motor and Pulley Lift System

Operational Mechanism

The operational mechanism of the motor-driven lift is relatively straightforward. The electric motor is powered, and the motor's rotation drives the pulleys, winding or unwinding the ropes, thus moving the lift car up or down within the shaft. The counterweights play an integral part by

providing balance, ensuring that the motor is not overly burdened with lifting the car's full weight, thus improving energy efficiency. Additionally, safety brakes are incorporated into the system to automatically engage in the event of a rope failure or other malfunction, preventing the lift car from falling and ensuring user safety.




Figure 0.5: Side view of Motor and Pulley Lift System

Advantages

One of the primary advantages of this system is its high load capacity. The motor-driven rope and pulley system is capable of transporting heavy loads across multiple floors, making it ideal for use in commercial buildings, residential complexes, and industrial facilities where higher weight capacities are needed. The counterweight mechanism also contributes to the lift's energy efficiency, as it reduces the amount of electrical energy required to operate the system.

Furthermore, the system's design is reliable and durable, and with proper maintenance, it can function efficiently for many years, providing a long-lasting solution for vertical transportation.

Limitations

However, despite its many benefits, the motor-driven rope and pulley system does have some limitations. The mechanical setup is relatively complex and requires precise alignment to ensure smooth operation. This complexity can increase installation time and costs, particularly in retrofit situations where the system is being installed in an existing structure. Moreover, the system demands higher maintenance compared to more straightforward pneumatic designs. Routine inspections of the pulleys, ropes, and motor components are necessary to maintain performance and avoid potential issues.

Applications

In terms of applications, the motor-driven rope and pulley lift is highly suited for multi-story buildings where load capacity and efficiency are top priorities. This system is widely used in commercial buildings, high-rise residential complexes, hospitals, and industrial facilities, where large volumes of passengers or heavy goods need to be transported across several floors. Additionally, it can be customized to meet the specific needs of different environments, including the addition of advanced features like smart control systems, emergency communication devices, and accessibility options for people with disabilities.

The Motor-Driven Rope and Pulley Lift Design remains one of the most reliable and efficient solutions for vertical transportation, particularly in multi-story applications. While it requires a more complex setup and higher maintenance than pneumatic systems, its high load capacity, energy efficiency, and proven durability make it a preferred choice for many building types. With

the right maintenance and proper installation, this system can provide many years of dependable service, ensuring safe and effective vertical movement for users.




Figure 0.6: Image of Motor and Pulley Lift System

Evaluation Criteria for the Lift Structure

The assessment of the Lift structure design must consider several critical factors to ensure optimal performance, safety, and cost efficiency. Key evaluation parameters include overall cost, operational accuracy and reliability, ease of integration, and adherence to safety standards. Each

of these aspects is essential in determining the system's effectiveness and suitability for its intended application.

Cost

The Motor-Driven Rope and Pulley Lift system is generally more expensive than alternative lift systems such as pneumatic or simpler mechanical designs, primarily due to the complexity of its components and the requirement for precise engineering. The initial installation cost is high, as it includes the motor, pulleys, ropes, counterweights, lift shaft construction, and related control systems. However, the system's long-term operational costs can be mitigated by its energy efficiency, especially when combined with an optimized counterweight mechanism that reduces the strain on the motor. While the upfront investment may be significant, the system's ability to handle heavy loads and operate for extended periods without major repairs makes it a cost-effective solution in the long run for large-scale applications.

Accuracy

In terms of operational accuracy, the Motor-Driven Rope and Pulley system provides a reliable and consistent performance. The motor-controlled pulleys offer precise control over the lift's vertical movement, ensuring that the lift car stops at the correct floor without overshooting or under-reaching. The counterweight system further contributes to the accuracy of the operation by balancing the lift car's weight, ensuring that the motor only needs to overcome the weight differential. This precise control of the lift's movement is essential in high-rise buildings, where accurate stopping at floors is critical for the safety and comfort of passengers. Limit switches and safety sensors further enhance accuracy by preventing over-travel and ensuring that the lift halts at the appropriate floor level.

Ease of Integration

The motor-driven rope and pulley lift system can be easily integrated into most building types, particularly those with existing vertical shafts, as long as there is sufficient space for the motor and pulley system at the top of the lift shaft. However, integration becomes more complex when retrofitting the system into an existing structure that was not originally designed to accommodate it. Modifications to the building may be required to create or adjust the lift shaft and space for the motor. In new constructions, the integration process is relatively straightforward, as the design and installation can be done according to the specifications of the building. The control system integration is also simplified with modern technologies, as the lift can be connected to centralized building management systems for monitoring and operation.

Safety

Safety is a primary concern when evaluating the Motor-Driven Rope and Pulley Lift Design. This system adheres to stringent safety standards such as the EN 81-20/50, ensuring compliance with regulations for lift design and operation. Key safety features include the use of mechanical safety brakes, which engage automatically in the event of a failure of the ropes or pulleys, preventing the lift car from free-falling. The limit switches at both the top and bottom of the lift shaft are another critical safety feature, ensuring that the lift car does not overshoot or fall below its designated stops. The counterweight system also adds an extra layer of safety, reducing the load on the motor and minimizing the risk of strain or mechanical failure. Furthermore, safety features such as

emergency communication systems and overload sensors can be added to ensure that passengers are safe in the event of a malfunction.

Summary

Cost: Motor-driven rope and pulley system > Pneumatic zigzag lift.

Accuracy: Motor-driven rope and pulley system > Pneumatic zigzag lift.

Ease of Integration: Pneumatic zigzag lift > Motor-driven rope and pulley system.

Safety: Both systems comply with EN 81-20/50 safety standards.

3.3.3 Decision Matrix for Pneumatic Zigzag Lift vs. Motor/Pulley System

When comparing the **Pneumatic Zigzag Lift** and the **Motor/Pulley System**, several criteria were considered to evaluate each concept's strengths and weaknesses. These criteria include **technical feasibility, functionality, capital/running cost, usability, and safety**. A score was assigned to each concept under each criterion, weighted accordingly, to provide an overall picture of their suitability. Here's an in-depth explanation of the assessment process:

Table 0.3: Decision Matrix for Lift Structure

Design Specs	Weighting	Pneumatic Zigzag Lift		Motor/Pulley System	
		Utility Score	Weighted Score	Utility Score	Weighted Score
Technical Feasibility	0.2	6	1.2	9	1.8
Functionality	0.25	8	2.0	10	2.5
Capital	0.2	6	1.2	6	1.2
Usability	0.15	7	1.05	10	1.5
Safety	0.2	9	1.8	10	2.0
Total Score	10		7.25		9.0

Technical Feasibility (20%)

The technical feasibility of each concept was analyzed based on how easily they could be implemented with current technology. The **Pneumatic Zigzag Lift** received a score of **6**, as it requires pneumatic components like air compressors, which introduce a level of complexity in both installation and maintenance. Additionally, integrating pneumatic systems can be more challenging compared to conventional mechanical systems. On the other hand, the **Gesture-Controlled Motor/Pulley System** scored **9** because it utilizes well-established motor and pulley

technology, which is proven, efficient, and relatively easy to implement using existing components.

Functionality (25%)

Functionality refers to how effectively each system performs its intended tasks. The **Pneumatic Zigzag Lift** scored **8**, offering smooth motion, but it is somewhat limited in its load capacity. It's ideal for low-load scenarios but not well-suited for applications requiring more significant lifting power. In contrast, the **Motor/Pulley System** scored the highest in functionality with a **10** because it's robust, versatile, and capable of handling a wide range of lifting tasks, including those required in multi-story buildings. It provides reliable performance for heavier loads and more complex operations.

Capital/Running Cost (20%)

The capital and running costs of each system were assessed to understand the financial investment needed to build and maintain them. Both systems received a score of **6** for this criterion, indicating a moderate level of cost. The **Pneumatic Zigzag Lift** involves pneumatic components, which can be expensive to source and maintain, but its simplicity helps keep overall costs down. Similarly, the **Motor/Pulley System** has a moderate to high initial cost, particularly with the gesture control and motor components, but the operational costs are balanced by the system's durability and low maintenance requirements.

Usability (15%)

Usability was considered in terms of how user-friendly and intuitive each system is for the end user. The **Pneumatic Zigzag Lift** received a score of **7** for usability. While it provides smooth motion, it may not be as intuitive for users, especially those unfamiliar with the operation of

pneumatic systems. On the other hand, the **Gesture-Controlled Motor/Pulley System** scored **10** for its ease of use. The gesture control feature makes it highly intuitive, allowing users to operate it with simple, touch-free gestures, thus increasing accessibility and comfort for all users, including those with physical limitations.

Safety (20%)

Safety is a critical consideration in any lifting system, and both concepts were evaluated for their compliance with safety standards and risk mitigation. The **Pneumatic Zigzag Lift** received a score of **9**, as it is generally safe with adequate mechanisms to prevent accidents. However, its limited load capacity might pose safety concerns under certain conditions. The **Motor/Pulley System** scored the highest with a **10** due to its built-in safety features such as travel limit switches and manual overrides, which ensure it operates within safe limits and can be controlled even in emergency situations.

Total Score: Pneumatic Zigzag Lift (7.25) vs. Motor/Pulley System (9.0)

After evaluating each criterion, the **Pneumatic Zigzag Lift** achieved a total score of **7.1**, while the **Gesture-Controlled Motor/Pulley System** scored **9.0**. The **Gesture-Controlled Motor/Pulley System** is the superior choice, especially when considering its higher functionality, usability, and safety. Although both systems are technically feasible and share similar capital/running costs, the motor/pulley system's versatility and user-friendliness make it the more advantageous option, especially for multi-story applications and environments requiring more robust performance.

3.3.4 Decision Matrix for Gesture Recognition System

The comparison of the three systems—IR Sensor Array, PAJ7620 Gesture Recognition Software, and Camera-Based System—was conducted based on five key criteria: technical feasibility, functionality, capital/running cost, usability, and safety. Below is the analysis and interpretation of the results.

Table 0.4: Design Matrix for Gesture Control

Design Specs	Weighting	IR Sensor Array		PAJ7620	PAJ7620	Camera-Based System	Camera-Based
		Utility Score	Weighted Score	Utility Score	Weighted Score	Utility Score	Weighted Score
Technical Feasibility	0.20	6	1.20	9	1.80	7	1.40
Functionality	0.25	7	1.75	9	2.25	10	2.50
Capital	0.20	9	1.80	7	1.40	5	1.00
Usability	0.13	6	0.90	9	1.35	8	1.20
Safety	0.20	9	1.80	10	2.00	9	1.80
Total Score	1	—	7.45	—	8.8	—	7.90

Technical Feasibility (Weight: 20%)

When assessing the technical feasibility, the PAJ7620 Gesture Recognition Software scored the highest with a 9, as it integrates easily with existing systems, and its technology is well-established and widely used. The Camera-Based System received a 7 due to its dependence on more sophisticated technology and higher computational requirements. The IR Sensor Array scored the lowest with a 6, as it requires more complex sensor integration and can face limitations in terms of range and accuracy.

Functionality (Weight: 25%)

In terms of functionality, the Camera-Based System stood out with a perfect score of 10. It offers highly versatile capabilities, detecting a wide range of gestures and allowing for advanced features such as gesture recognition at varying distances. The PAJ7620 Gesture Recognition Software, with a score of 9, provides a solid and accurate recognition experience but lacks the wide versatility of the Camera-Based System. The IR Sensor Array, receiving a score of 7, has limited functionality, mainly constrained by its range and sensitivity.

Capital/Running Cost (Weight: 20%)

When it comes to capital and running costs, the IR Sensor Array is the most cost-effective, scoring 9 due to its low initial investment and inexpensive operation. The PAJ7620 Gesture Recognition Software scored 8, which is still relatively affordable but costs more than the IR Sensor Array due to its more complex hardware requirements. The Camera-Based System, with a score of 5, has the highest costs, including hardware expenses and computational needs, making it the least budget-friendly option.

Usability (Weight: 15%)

Regarding usability, the PAJ7620 Gesture Recognition Software scored the highest at 9. It is user-friendly and integrates seamlessly into existing systems, offering a smooth experience. The Camera-Based System followed with a score of 8, providing advanced features but requiring more setup and user interaction. The IR Sensor Array, with a score of 6, is less intuitive and may require additional setup to function as desired.

Safety (Weight: 20%)

In terms of safety, all three systems performed well, but the PAJ7620 Gesture Recognition Software scored a perfect 10. Its non-invasive technology, with no direct physical interaction, makes it a safer option overall. The Camera-Based System also scored highly at 9, though there are concerns about privacy and surveillance. The IR Sensor Array, while not as intrusive, also scored 9 due to its minimal risks and non-invasive nature.

Interpretation of Results

The PAJ7620 Gesture Recognition Software emerges as the best option overall, scoring the highest in technical feasibility, functionality, usability, and safety. Despite being more expensive than the IR Sensor Array, it offers the best balance between performance and cost-effectiveness for most applications.

The Camera-Based System, while highly functional and capable of more advanced features, comes at a significantly higher cost and complexity, which limits its practicality for budget-conscious or less technically demanding projects. However, its advanced capabilities make it a strong contender for specialized use cases.

The IR Sensor Array, although the most cost-effective, offers limited functionality and is less user-friendly compared to the other two systems. It is best suited for projects where cost is the primary consideration, and advanced features are not needed.

3.4. SELECTION OF CONCEPTS

3.4.1 LIFT STRUCTURE

In evaluating these two concepts, the **Gesture-Controlled Motor/Pulley System** proves to be the superior choice. While the **Pneumatic Zigzag Lift** offers smooth operation and moderate safety features, it is limited in terms of **load capacity** and **technical complexity**. Additionally, its **usability** is less intuitive compared to the **gesture-controlled system**, which provides a more **user-friendly, versatile, and safer option** for modern lift systems.

The **gesture-controlled system** not only outperforms the pneumatic option in functionality and usability but also incorporates more advanced **safety mechanisms**. Furthermore, the **motor/pulley system's versatility** makes it suitable for a broader range of applications, including multi-story buildings, where load capacity and reliability are critical.

3.4.2 GESTURE RECOGNITION AND CONTROL MECHANISM

After a thorough evaluation of all three concepts, it becomes clear that the **PAJ7620 Gesture Recognition Software** stands out as the most suitable choice for most practical lift systems. This selection is based on its ability to provide **reliable accuracy** while maintaining a **moderate cost**. It also offers the significant advantage of **simple integration** into existing control systems, making it easier to incorporate into current infrastructure. Additionally, the **balanced performance** of the

PAJ7620 ensures that it meets the needs of most users without introducing the **complexity** and **high cost** associated with the camera-based system.

In contrast, while the **IR sensor array** does offer a **cost-effective solution**, its **limited accuracy** can be a drawback, particularly in applications where precision is a critical factor. On the other hand, the **camera-based system**, although offering the **highest accuracy**, may be seen as **overkill** for general lift systems due to its **high cost** and the **complexity** involved in its integration. The **PAJ7620**, therefore, represents the most **pragmatic choice**, offering an ideal balance of **cost**, **accuracy**, and **ease of implementation**, making it the optimal solution for most applications.

THE MOTOR/PULLEY SYSTEM AND PAJ7620 GESTURE RECOGNITION MECHANISM ARE THE BEST CHOICES FOR THE LIFT SYSTEM.

THE MOTOR/PULLEY SYSTEM OFFERS BETTER SAFETY, VERSATILITY, AND USABILITY, MAKING IT SUITED FOR MULTI-STORY BUILDINGS.

THE PAJ7620 PROVIDES A RELIABLE, COST-EFFECTIVE SOLUTION WITH EASY INTEGRATION, STRIKING A BALANCE BETWEEN ACCURACY AND COST, MAKING IT THE MOST PRACTICAL CHOICE OVER OTHER OPTIONS.

3.4 DETAILED DESIGN

3.5.1 DESIGN CALCULATIONS

1. Load Calculations for Gesture-Controlled Motor/Pulley System

According to Design Specs:

Maximum Load Capacity: 500 kg (including the lift platform and users).

Lift Height: 10 meters (for a multi-story building).

Efficiency of Motor/Pulley System: 90% (to account for friction and mechanical losses).

Safety Factor: 1.5. *Khan, Z. (2016, December 30).*

Motor Speed: 0.5 m/s (standard lift speed).

Formulas

1. Force Required to Lift the Load:

$$F = m \times g$$

here:

m = Mass of the load (500 kg).

g = Acceleration due to gravity (9.81 m/s²).

2. Power Required for the Motor:

$$P = \frac{F \times v}{\eta}$$

ere:

P = Power (in Watts).

F = Force (in Newtons).

v = Lift speed (in m/s).

η = Efficiency of the motor/pulley system (90% or 0.9).

3. Torque Required for the Motor:

$$T = \frac{F \times r}{\eta}$$

here:

T = Torque (in Newton-meters).

F = Force (in Newtons).

r = Radius of the pulley (in meters).

η = Efficiency of the motor/pulley system (90% or 0.9).

Calculations

1. Force Required to Lift the Load:

$$F = m \times g = 500 \text{ kg} \times 9.81 \text{ m/s}^2 = 4905 \text{ N}$$

2. Power Required for the Motor:

$$P = \frac{F \times v}{\eta} = \frac{4905 \text{ N} \times 0.5 \text{ m/s}}{0.9} = 2736.11 \text{ W} = 2.73 \text{ kW}$$

3. Torque Required for the Motor:

Assume the radius of the pulley is **0.1 m** (10 cm).

Torque (T):

$$T = \frac{F \times r}{\eta} = \frac{4905 \text{ N} \times 0.1 \text{ m}}{0.9} = 490.5 \text{ Nm}$$

Summary

Force Required: 4905 N.

Motor Power: 2.73 kW.

Motor Torque: 490.5 Nm.

Table 0.5: Comparison of Load Calculations

Parameter	Pneumatic Zigzag Lift	Gesture-Controlled Motor/Pulley System
Maximum Load Capacity	150 kg	500 kg
Force Required	1471.5 N	4905 N
Pressure/Torque	6.62 bar	490.5 Nm
Power Required	N/A	2.73 kW
Application	Lightweight applications	Multi-story buildings

The **Pneumatic Zigzag Lift** is suitable for **lightweight applications** with a maximum load capacity of **150 kg**. It requires a pneumatic pressure of **6.62 bar** to operate effectively.

The **Gesture-Controlled Motor/Pulley System** is designed for **heavier loads** (up to **500 kg**) and is ideal for **multi-story buildings**. It requires a motor with a power rating of **2.73 kW** and a torque of **490.5 Nm**.

2. Motor Power Calculation

Maximum Load Capacity: 500 kg (including the lift platform and users).

Lift Speed: 0.5 m/s (standard lift speed).

Lift Height: 10 meters (for a multi-story building).

Efficiency of the System: 90% (to account for friction and mechanical losses).

Safety Factor: 1.5 *Khan, Z. (2016, December 30).*

Acceleration Due to Gravity (g): 9.81 m/s² (standard value for gravity).

Formulas:

1. Force Required to Lift the Load:

$$F = m \times g$$

here:

F = Force (in Newtons).

m = Mass of the load (in kg).

g = Acceleration due to gravity (9.81 m/s²).

2. Power Required for the Motor (without considering efficiency):

$$P = \frac{F \times v}{\eta}$$

here:

P = Power (in Watts).

F = Force (in Newtons).

v = Lift speed (in m/s).

η = Efficiency of the system (as a decimal, i.e., 0.9 for 90%).

3. Motor Power with Safety Factor:

$$P_{\text{motor}} = P \times \text{Safety Factor}$$

here:

P_{motor} = Motor power required (in Watts).

P = Power required (in Watts).

Safety Factor = 1.5.

4. Torque Requirement (based on the pulley radius):

$$T = \frac{F \times r}{\eta}$$

here:

T = Torque (in Nm).

F = Force (in Newtons).

r = Radius of the pulley (in meters).

η = Efficiency of the system (as a decimal).

Calculations:

1. Force Required to Lift the Load:

$$F = m \times g = 500 \text{ kg} \times 9.81 \text{ m/s}^2 = 4905 \text{ N}$$

2. Power Required for the Motor:

$$P = \frac{F \times v}{\eta} = \frac{4905 \text{ N} \times 0.5 \text{ m/s}}{0.9} = 2725 \text{ W (or 2.725 kW)}$$

3. Motor Power with Safety Factor:

$$P_{\text{motor}} = 2725 \text{ W} \times 1.5 = 4087.5 \text{ W (or 4.1 kW)}$$

This is the minimum power required for the motor, rounded to 4.1 kW for safety.

4. Torque Requirement:

With radius of the pulley is 0.1 m:

$$T = \frac{F \times r}{\eta} = \frac{4905 \text{ N} \times 0.1 \text{ m}}{0.9} = 490.5 \text{ Nm}$$

Motor Selection:

Required Motor Power: 4.1 kW (rounded up for safety).

Motor Type: A 3-phase AC induction motor or a brushless DC motor with a power rating of 4.1 kW and a speed of 0.5 m/s is recommended.

Torque Requirement: The motor must provide a minimum torque of **490.5 Nm** to lift the load effectively.

Table 0.6: Summary of Motor Specifications

Parameter	Value
Motor Power	4.1 kW
Motor Type	3-phase AC induction or brushless DC motor
Lift Speed	0.5 m/s
Torque	490.5 Nm
Efficiency	90%
Safety Factor	1.5 Khan, Z. (2016, December 30).

The **Gesture-Controlled Motor/Pulley System** requires a motor with a **power rating of 4.1 kW** and a **torque of 490.5 Nm** to lift a maximum load of **500 kg** at a speed of **0.5 m/s**. These calculations ensure the motor is capable of handling the load safely and efficiently, even with a safety factor applied.

3. Pulley and Rope Design for Gesture-Controlled Motor/Pulley System

Maximum Load Capacity: 500 kg (including the lift platform and users).

Lift Speed: 0.5 m/s.

Lift Height: 10 meters.

Number of Pulleys: 2 (one fixed and one movable).

Safety Factor: 8 *Safety Culture Content Team. (2024, April 8).*

Material: Aluminum wire rope (common for lift systems).

Pulley Material: Cast iron or aluminum (for durability).

Formulas

1. Tension in the Rope:

$$T = \frac{m \times g}{n}$$

where:

T = Tension in the rope (in Newtons).

m = Mass of the load (in kg).

g = Acceleration due to gravity (9.81 m/s²).

n = Number of supporting ropes (assumed to be 2 for a single movable pulley system).

2. Rope Diameter:

$$d = \sqrt{\frac{4 \times T}{\pi \times \sigma}}$$

here:

d = Diameter of the rope (in meters).

σ = Allowable stress of the rope material (for steel wire rope, $\sigma = 500 \text{ MPa} = 500 \times 10^6 \text{ Pa}$).

3. Pulley Diameter:

$$D = 12 \times d$$

here:

D = Diameter of the pulley (in meters).

d = Diameter of the rope (in meters).

4. Bending Stress on the Rope:

$$\sigma_b = \frac{T}{d \times E}$$

ere:

σ_b = Bending stress (in Pascals).

E = Modulus of elasticity of the rope material (for steel, $E = 200 \text{ GPa} = 200 \times 10^9 \text{ Pa}$).

T = Tension in the rope (in Newtons).

d = Diameter of the rope (in meters).

Calculations

1. Tension in the Rope:

$$T = \frac{m \times g}{n} = \frac{500 \text{ kg} \times 9.81 \text{ m/s}^2}{2} = 2452.5 \text{ N}$$

The tension in the rope is 2452.5 N.

2. Rope Diameter:

$$d = \sqrt{\frac{4 \times 2452.5 \text{ N}}{\pi \times 500 \times 10^6 \text{ Pa}}} = \sqrt{\frac{9809.9}{1.5708 \times 10^9}} = 0.00224 \text{ m} = 2.24 \text{ mm}$$

Rounding up for safety, the **selected rope diameter** is **6 mm**.

3. Pulley Diameter:

$$D = 12 \times d = 12 \times 0.006 \text{ m} = 0.072 \text{ m} = 72 \text{ mm}$$

Selected pulley diameter is **120 mm** for added safety and durability.

4. Bending Stress on the Rope:

$$\sigma_b = \frac{T}{d \times E} = \frac{2452.5 \text{ N}}{0.006 \text{ m} \times 200 \times 10^9 \text{ Pa}} = \frac{2452.5}{1.2 \times 10^9} = 2.04 \text{ MPa}$$

The bending stress is **2.04 MPa**, which is well below the allowable stress of the rope material (500 MPa), ensuring safety.

Table 0.7: Summary of Pulley and Rope Specifications

Parameter	Value
Rope Diameter	6 mm
Rope Material	Aluminum wire rope
Pulley Diameter	120 mm
Pulley Material	Cast iron or aluminum
Tension in Rope	2452.5 N
Bending Stress	2.04 MPa
Safety Factor	8 <i>Safety Culture Content Team. (2024, April 8).</i>

The **pulley and rope design** for the **Gesture-Controlled Motor/Pulley System** includes:

A **6 mm diameter aluminum wire rope** capable of handling a tension of **2452.5 N** with a safety factor of **8**.

A **120 mm diameter pulley** made of cast iron or aluminum to minimize bending stress on the rope.

4. Structural Design Calculations for Gesture-Controlled Motor/Pulley System

Maximum Load Capacity: 500 kg (including the lift platform and users).

Lift Platform Dimensions: 1.5 m (length) $\times$ 1 m (width).

Material: Structural aluminum (yield strength $\sigma_y=250$ MPa).

Safety Factor: 5 *Safety Culture Content Team. (2024, April 8).*

Acceleration Due to Gravity (gg): 9.81 m/s^2 .

Load Distribution

The total load is distributed across the **lift platform** and **support structure**.

1. Total Load:

$$W = 500 \times 9.81 = 4905 \text{ N}$$

2. Load per Unit Area:

$$w = \frac{4905}{1.5 \times 1} = 3270 \text{ N/m}^2$$

Lift Platform Design

The lift platform is made of **aluminum plates** supported by **aluminum beams**.

1. Thickness of Aluminum Plate:

$$\text{Volume} = 1.5 \times 1 \times 0.01 = 0.015 \text{ m}^3$$

$$\text{Mass} = 0.015 \times 7850 = 117.75 \text{ kg}$$

$$\text{Weight} = 117.75 \times 9.81 = 1154 \text{ N}$$

Total load including the platform:

$$W_{\text{total}} = 4905 + 1154 = 6059 \text{ N}$$

2. Bending Stress on the Platform:

Assume the platform is simply supported at the edges.

Maximum bending moment (MM):

$$M = \frac{wL^2}{8} = \frac{(3270 \times 1.5^2)}{8} = 918.28 \text{ Nm}$$

Where:

- w = Load per unit length (3270 N/m).
- L = Length of the platform (1.5 m).

Section modulus (ZZ) for the aluminum plate:

$$Z = \frac{bt^2}{6} = \frac{1 \times (0.01)^2}{6} = 1.67 \times 10^{-5} \text{ m}^3$$

Where:

b = Width of the platform (1m).

t = Thickness of the plate (0.01m).

Bending stress (σ_b):

$$\sigma_b = \frac{M}{Z} = \frac{918.28}{1.67 \times 10^{-5}} = 55.1 \text{ MPa}$$

The bending stress (**55.1 MPa**) is well below the yield strength of aluminum (**250 MPa**), ensuring safety.

Support Structure Design

The support structure consists of **vertical aluminum columns** and **horizontal beams**.

1. Load on Each Column:

The load is evenly distributed across **4 columns**.

Load per column:

$$P_{\text{column}} = \frac{6059}{4} = 1514.75 \text{ N}$$

2. Column Design:

Assume the columns are made of **square hollow aluminum sections** with a side length of **50 mm** and a thickness of **5 mm**.

Cross-sectional area (A):

$$A = (50 \times 50) - (40 \times 40) = 900 \text{ mm}^2 = 9 \times 10^{-4} \text{ m}^2$$

Stress on the column:

$$\sigma = \frac{P}{A} = \frac{1514.75}{9 \times 10^{-4}} = 1.68 \text{ MPa}$$

The stress (**1.68 MPa**) is well below the yield strength of aluminum (**250 MPa**), ensuring safety.

Table 0.8: Summary of Structural Design

Component	Specifications
Lift Platform	10 mm thick aluminum plate
Total Load	6059 N
Support Columns	50 mm square hollow aluminum section
Bending Stress (Platform)	55.1 MPa (safe)
Stress on Columns	1.68 MPa (safe)
Safety Factor	5

The **structural design** of the **Gesture-Controlled Motor/Pulley System** ensures that the **lift platform** and **support structure** can safely handle the maximum load of **500 kg**. The bending

stress on the platform and the stress on the columns are well within the allowable limits for structural aluminum.

5. Brake System Design

Brake System Design for Gesture-Controlled Motor/Pulley System

Maximum Load Capacity: 500 kg (including the lift platform and users).

Lift Speed: 0.5 m/s.

Brake Response Time: 0.5 seconds (to bring the lift to a complete stop).

Pulley Diameter: 120 mm

Safety Factor: 2 (to ensure the brake can handle unexpected loads).

Coefficient of Friction (μ): 0.3 (for brake pads and drum).

Formulas

1. Deceleration Required:

$$a = \frac{v}{t} = \frac{0.5}{0.5} = 1 \text{ m/s}^2$$

Where:

a = Deceleration (in m/s²).

v = Lift speed (in m/s).

t = Brake response time (in seconds).

2. Brake Force Required:

$$F_{\text{brake}} = m \times a = 500 \times 1 = 500 \text{ N}$$

Where:

F_{brake} = Brake force (in Newtons).

m = Mass of the load (in kg).

3. Brake Torque Required:

Radius of the pulley (r):

$$r = \frac{\text{Pulley Diameter}}{2} = \frac{120}{1000} \div 2 = 0.06 \text{ m}$$

$$T_{\text{brake}} = F_{\text{brake}} \times r = 500 \times 0.06 = 30 \text{ Nm}$$

Where:

T_{brake} = Brake torque (in Nm).

r = Radius of the pulley (in meters).

4. Brake Pad Force:

$$F_{\text{pad}} = \frac{T_{\text{brake}}}{\mu \times R}$$

$$F_{\text{pad}} = \frac{60}{0.3 \times 0.06} = \frac{60}{0.018} = 1666.67 \text{ N}$$

Where:

F_{pad} = Force applied by the brake pads (in Newtons).

R = Effective radius of the brake drum (assume equal to the pulley radius).

Brake Selection

Brake Type: Electromagnetic Brake or Disc Brake with a minimum torque rating of **60 Nm**.

Brake Pad Force: **1666.67 N** (to ensure sufficient friction for stopping).

Brake Response Time: **0.5 seconds** (to meet safety requirements).

Table 0.9: Summary of Brake System Specifications

Parameter	Value
Brake Torque Required	60 Nm
Brake Type	Electromagnetic or Disc Brake
Brake Pad Force	1666.67 N
Brake Response Time	0.5 seconds
Safety Factor	2

The **brake system design** for the **Gesture-Controlled Motor/Pulley System** includes:

A **brake with a torque rating of 60 Nm** to safely stop the lift under maximum load conditions.

Brake pads capable of applying a force of 1666.67 N to ensure sufficient friction.

A **response time of 0.5 seconds** to meet safety requirements.

6. Acceleration and Deceleration Calculations

Maximum Load Capacity: 500 kg (including the lift platform and users).

Lift Speed: 0.5 m/s (constant speed during operation).

Acceleration Time: 1 second (time to reach the constant speed).

Deceleration Time: 0.5 seconds (time to bring the lift to a complete stop).

Motor Power: 4.1 kW (from previous calculations).

Safety Factor: 1.5 (to ensure the system can handle unexpected loads)

Formulas

1. Acceleration (aa):

$$a = \frac{v}{t} = \frac{0.5}{1} = 0.5 \text{ m/s}^2$$

Where:

a = Acceleration (in m/s^2).

v = Lift speed (in m/s).

t = Time to reach the constant speed (in seconds).

2. Force Required for Acceleration (F_{acc}):

$$F_{acc} = m \times a = 500 \times 0.5 = 250 \text{ N}$$

Where:

F_{acc} = Force required for acceleration (in Newtons).

m = Mass of the load (in kg).

3. Power Required for Acceleration (P_{acc}):

$$P_{acc} = F_{acc} \times v = 250 \times 0.5 = 125 \text{ W}$$

Where:

P_{acc} = Power required for acceleration (in Watts).

4. **Deceleration (a_{dec}):**

$$a_{\text{dec}} = \frac{v}{t_{\text{dec}}} = \frac{0.5}{0.5} = 1 \text{ m/s}^2$$

Where:

a_{dec} = Deceleration (in m/s²).

t_{dec} = Time to bring the lift to a complete stop (in seconds).

5. **Force Required for Deceleration (F_{dec}):**

$$F_{\text{dec}} = m \times a_{\text{dec}} = 500 \times 1 = 500 \text{ N}$$

Where:

F_{dec} = Force required for deceleration (in Newtons).

Table 0.10: Summary of Acceleration and Deceleration

Parameter	Acceleration	Deceleration
Time	1 second	0.5 seconds
Acceleration/Deceleration	0.5 m/s ²	1 m/s ²
Force Required	250 N	500 N
Power Required	125 W	N/A

Acceleration: The lift accelerates at **0.5 m/s²** to reach its constant speed of **0.5 m/s** in **1 second**, requiring a force of **250 N** and a power of **125 W**.

Deceleration: The lift decelerates at **1 m/s²** to come to a complete stop in **0.5 seconds**, requiring a force of **500 N**.

3.5 MANUFACTURING SPECIFICATION

Table 0.11: Manufacturing Specification

Component	Specification
Motor	Type: Industrial Stepper Motor
	Rated Power: 500 W
	Rated Voltage: 220 V AC
	Rated Current: 3 A
	Torque: 15 Nm
	Speed: 1 m/s
	Efficiency: 90%
	Motor Shaft Diameter: 12 mm

Component	Specification
	Cooling: Active (Cooling fan or liquid cooling for high power)
	Mounting Type: Flanged or shaft-mounted
Pulley	Material: Aluminum or High-strength Aluminum Alloy
	Diameter: 200 mm
	Groove Type: V-groove or custom groove based on rope system
	Width: 60 mm
	Load Capacity: 1000 kg (depending on system design)
	Bearing Type: Heavy-duty ball bearing or roller bearing
	Mounting Type: Shaft-mounted
	Finish: Anodized for light weight and corrosion resistance or powder-coated
Rope	Material: Galvanized Aluminum or Polyester-coated Aluminum (for heavy-duty lifting applications)
	Diameter: 10 mm
	Breaking Strength: 5000 kg

Component	Specification
	Length: Customizable based on lift height (typically 10-30 meters)
	Flexibility: High flexibility for smooth operation in pulleys
Brake System	Type: Electric or Hydraulic Brake
	Torque: 50 Nm (customizable based on load)
	Pad Material: Carbon composite or high-performance friction material
	Operating Voltage: 220 V AC
	Response Time: 2 seconds
	Mounting Type: Mounted on motor shaft or pulley system
Lift Platform	Material: Heavy-duty Aluminum or Aluminum
	Dimensions: 2 m x 3 m (customizable based on load)
	Surface Finish: Anti-slip, textured aluminum plate or rubber mat for safety
	Weight: 200 kg – 500 kg depending on the platform size
	Structural Support: Reinforced aluminum frame for stability and strength

Component	Specification
Structural Frame	Material: Reinforced Aluminum or High-strength Aluminum
	Column Type: Heavy-duty aluminum or aluminum tube with larger cross-sectional area
	Wall Thickness: 5-10 mm depending on structural strength
	Length: Customizable to accommodate lift height (typically 10-20 meters)
	Finish: Powder-coated for protection against corrosion
Control System	Controller Type: Advanced PLC (Programmable Logic Controller) or Industrial-grade ESP32/Arduino with wireless control
	Input Voltage: 220 V AC or 12 V DC (depending on the system power requirements)
	Inputs: Gesture recognition sensor (PAJ7620 or advanced sensor), limit switches, emergency stop button, speed and direction control
	Outputs: Motor control signals, brake control, lift position signals, safety alerts
	Communication Protocol: I2C, UART, Modbus TCP/IP, or RS-485 (depending on system setup)

Component	Specification
	Sensors: PAJ7620 Gesture Sensor, Ultrasonic proximity sensors, Load sensors, Limit switches
	Control Display: Industrial-grade touch screen or physical buttons with LCD/LED indicators for status and diagnostics
	Power Supply: 220 V AC or backup generator for continuous operation
Safety Specifications	Overload Protection: Integrated in control system with load sensing, automatic shut-off at predefined overload thresholds
	Emergency Stop: Manual emergency button and automatic emergency stop system in case of fault
	Safety Limit Switches: Installed at top and bottom of travel path to prevent over-extension of lift platform
	Emergency Brake: Automatically engages in case of system failure, power loss, or excessive load
	Noise Level: Below 80 dB during operation
Assembly Considerations	Tolerances: ± 0.5 mm for precision parts, ± 2 mm for structural components

Component	Specification
	Welding: MIG or TIG welding for frame assembly; bolt-on design for easy assembly and maintenance
	Assembly Type: Modular assembly with detailed instructions; adjustable components for customized installations
	Testing: Load testing, motor efficiency testing, and safety feature checks (limit switches, emergency brakes, and sensors)
Packaging and Shipping	Packaging Type: Wooden crates with foam padding or custom packaging for sensitive components (e.g., control system, motors)
	Shipping Method: Ground shipping for local transport or air freight for international delivery
	Handling Instructions: Handle motors, electronics, and sensors with care to avoid damage or misalignment

3.6 CONSTRUCTION AND MANUFACTURING

Initial Planning and Design

We began by brainstorming and conceptualizing the **gesture-controlled lift system**. We discussed the key components required for the conceptual model, such as the **stepper motor**, **pulley system**, **gesture sensor (PAJ7620)**, and **control system (ESP32 microcontroller)**. We created detailed

CAD drawings to define the frame structure, pulley placements, and electrical connections. We also established the specifications for each component, ensuring the conceptual model would be functional yet cost-effective.

Sourcing and Procurement

Once the design was finalized, we sourced all necessary materials and components. This involved selecting a **high-power stepper motor**, **aluminum pulleys**, **aluminum sheets** for the frame, **cables**, and **gesture sensors**. We also acquired **wires**, **relays**, and **connectors** to establish the electrical network. We worked to ensure that we had all the materials required for the build, keeping track of budget and delivery timelines.

Motor Assembly

We took charge of the motor assembly. We mounted the **stepper motor** onto the frame using **aluminum brackets** and ensured it was securely fastened. We used **high-torque motors** to ensure the lift could handle significant weights. After connecting the motor's power supply and wiring, we tested the motor's functionality to ensure it responded smoothly to inputs from the control system.

Pulley System Assembly

We then proceeded with assembling the **pulley system**. We used **aluminum pulleys** for their strength and durability. The pulleys were mounted onto the frame using **bearings** to reduce friction. We carefully routed the rope through the pulleys, ensuring that it was taut and aligned correctly for smooth motion. The rope selected for the conceptual model was a **high-strength polyester-coated cable**, which we cut to length and installed without slack to prevent any operational delays.

Gesture Sensor Integration

We continued with integrating the **gesture sensor (PAJ7620)** with the system. We connected the sensor to the **ESP32 microcontroller** via **I2C communication**, ensuring the sensor could detect gestures in the required range. After calibrating the sensor, we wrote the firmware to process the gestures. The gesture sensor was installed on the frame in a position where it could reliably detect hand movements in front of the system. Extensive testing was performed to ensure the sensor accurately recognized **upward** and **downward gestures**, sending the correct signals to the control system.

Control System Setup

With the motor, pulley system, and gesture sensor in place, we focused on the **ESP32 microcontroller**. We wrote the program that would process the signals from the gesture sensor and send commands to the stepper motor. The ESP32 was also connected to **relay circuits** to control the motor's direction and speed. We thoroughly tested the control system to ensure that **upward** gestures triggered an upward motion, and **downward** gestures activated downward movement.

Frame and Structural Support

Simultaneously, we worked on fabricating the frame for the conceptual model. We used **aluminum** for its lightweight properties, ensuring the system was easy to handle while still strong enough to support the motor, pulleys, and lift platform. The frame was welded together with precision to ensure it was level and square. The lift mechanism's alignment was double-checked to ensure smooth operation without binding or excessive wear.

Platform Construction and Safety Features

We designed and built the **lift platform**. We used **reinforced aluminum** to ensure the platform was both strong and lightweight. The platform was fitted with **safety rails** to prevent accidents and **non-slip surfaces** to ensure user safety during operation. The platform was then mounted to the lift system and tested for stability and smoothness in vertical motion.

Wiring and Electrical Integration

Once all mechanical components were assembled, we continued by wiring the entire system. We made sure that all connections were properly insulated and securely fastened. The control system was integrated with the motor, gesture sensor, and relay circuits. The **power supply** was also connected to the entire system, ensuring consistent voltage and current flow.

Testing and Calibration

After assembling the conceptual model, we conducted several rounds of **testing**. We performed **initial calibration** of the gesture sensor, ensuring that hand gestures were detected accurately. The system's response to gestures was then fine-tuned by adjusting the motor's speed and the brake's engagement. The lift was loaded with test weights to ensure the motor could handle the required loads without stalling. During this phase, we made several adjustments to improve the system's responsiveness and safety features.

CHAPTER FOUR – RESULTS AND DISCUSSION

This chapter presents the experimental findings from testing the conceptual model under various conditions, focusing on gesture sensor calibration, load testing, motor efficiency, and control system responsiveness. The following sections provide a detailed narrative supported by quantitative data and tables summarizing the test outcomes.

4.1 Gesture Recognition Performance

During our testing sessions, we were notably impressed by the strong performance of the gesture control system. In one instance, a simple hand wave was instantly recognized and the system promptly responded, offering a fluid and intuitive interaction. This quick response reinforced our confidence in the potential of the system for real-world applications. While we observed occasional challenges in low-light conditions, the system still maintained a high recognition accuracy and latency well within acceptable limits. These findings highlight the reliability of the system, and its ability to effectively interpret user gestures in various environments, confirming its practicality for future use in diverse settings.

During our testing sessions, we were highly impressed with the performance of our gesture control system. We recall a particular instance where a simple hand wave was recognized almost instantaneously, with the system responding with remarkable precision and speed. This near-instantaneous reaction not only underscored the efficacy of our underlying algorithms but also bolstered our confidence in the system's potential for real-world applications.

Despite encountering a few minor challenges under suboptimal lighting conditions—where recognition occasionally experienced slight delays—the overall performance in terms of accuracy and low latency remained commendable. These observations have provided us with

valuable insights into the system's operational dynamics, highlighting both its strengths and areas for further enhancement.

4.2 Gesture Sensor Calibration and Testing

The initial phase of testing concentrated on calibrating the gesture sensor to ensure accurate detection of hand movements. Calibration involved adjusting sensitivity thresholds and fine-tuning sensor parameters to reliably recognize both upward and downward gestures, even under varying lighting conditions.

The calibration process began with meticulous sensitivity adjustments. The sensor's trigger threshold was precisely set at 3.2 V, balancing responsiveness with effective noise reduction. This careful calibration ensured the sensor could distinguish between intentional hand movements and background disturbances. Extensive testing revealed that the sensor responded within an average of 150 milliseconds, enabling near real-time interaction. Over multiple iterations of testing and fine-tuning, the system's recognition accuracy was refined to an impressive 96%, ensuring that nearly all intended gestures were correctly identified.

These results align with findings from Yu et al. (2020), who demonstrated that infrared sensing at a 20 cm distance achieved an average hand gesture recognition accuracy of 96%. Similarly, Czuszyński et al. (2017) reported that optical linear sensors could efficiently detect hand poses with an accuracy of 98.76% under favorable lighting conditions. These studies corroborate the effectiveness of precise calibration and the impact of environmental factors on sensor performance.

Table 0.1: Gesture Sensor Calibration Results

Parameter	Test Value	Observation
Trigger Voltage	3.2 V	Optimized threshold for varied lighting
Response Time	150 MS	Near real-time processing
Recognition Accuracy	96%	High accuracy after calibration

4.3 Motor Efficiency and Control System Responsiveness

The motor efficiency tests focused on evaluating the motor's response to commands from the control system, ensuring that upward and downward motions were executed smoothly. The control system was designed to interpret gesture sensor outputs and translate them into precise motor commands.

4.2.1 Motor Efficiency and Control System Responsiveness

During the testing phase, several key outcomes were observed that underscored the efficiency and responsiveness of the integrated control system.



Figure 0.1: Fabricated structure of the model

Directional Response

Upward gestures reliably initiated an upward motion, while downward gestures triggered a corresponding descent. This precise response to directional commands confirms the effective

integration between the gesture sensor and the control system, ensuring that user inputs are accurately and promptly translated into mechanical movements.

Speed Adjustment

Fine-tuning of the motor speed settings resulted in a smoother acceleration and deceleration profile. By optimizing the motor’s response curves, the system effectively reduced abrupt jerks during operation. This adjustment not only improved the overall fluidity of the lift's motion but also contributed to a more comfortable and controlled user experience.

Efficiency Metrics

Efficiency testing revealed that the motor demonstrated a current consumption of approximately 1.5 A under nominal load conditions. This level of current draw is indicative of energy-efficient operation, ensuring that the system maintains a balance between performance and power consumption, which is critical for prolonged operational cycles.

Test Aspect	Value/Setting	Outcome
Upward Motion Trigger	Gesture sensor input	Consistent and reliable
Downward Motion Trigger	Gesture sensor input	Consistent and reliable
Motor Speed Setting	0.48–0.55 m/s	Smooth transition between speeds
Current Consumption	~1.5 A	Efficient performance

Figure 0.2: Motor Efficiency and Control Response

These findings indicate that the integration between the sensor and control system was successful, with the motor responding smoothly to the varying commands.

4.4 Discussion of Results

The results from the various tests indicate that the conceptual model meets the design requirements for responsiveness and load handling. The gesture sensor calibration achieved a high level of accuracy, while the load tests demonstrated that the mechanical system could reliably handle increased weight after minor adjustments. The motor efficiency tests and the integrated control system ensured that the device operates smoothly and responds correctly to user inputs.

The comprehensive testing and analysis reveal several key insights into the conceptual model's performance and integration:

Integration Success:

The seamless integration of the gesture sensor, control system, and mechanical components stands as a clear testament to the iterative design improvements made throughout development. Each element of the system worked in unison, ensuring that inputs were accurately processed and translated into smooth mechanical actions.

Areas for Improvement:

While the overall stability was maintained under most test conditions, the presence of slight oscillations, particularly under the higher end of the test load range, suggests that there is room for

further mechanical reinforcement. Incorporating additional damping mechanisms could help in mitigating these minor instabilities and enhance the system's robustness.

Future Work:

Looking ahead, continued refinements are essential. Optimizing the sensor algorithms to further improve gesture recognition accuracy, as well as reinforcing mechanical components, will be critical steps. These adjustments are expected to not only bolster system reliability but also pave the way for a more efficient and resilient design in subsequent iterations.

Overall, the results confirm that the conceptual model is on a promising path, with clear directions for improvements that will contribute to its future development and potential commercialization.

CHAPTER 5 - CONCLUSION AND RECOMMENDATION

5.1 Conclusion

This project has successfully demonstrated the feasibility of designing and manufacturing a gesture-controlled lift. Through a series of design iterations and conceptual model tests, the project achieved significant technical milestones. The system's integration of sensor technologies with control algorithms has resulted in a reliable and responsive lift conceptual model. The achievements include the development of a robust gesture recognition module, the successful interfacing of this module with the lift's control system, and the creation of a conceptual model that meets performance standards. These outcomes not only validate the design approach but also highlight the potential of gesture-based controls as a future trend in automated lift systems.

The project also provided valuable insights into the challenges of integrating cutting-edge sensor technology with mechanical systems. Continuous testing and iterative improvements allowed for the refinement of both hardware and software components. This iterative process improved system reliability and set the stage for future enhancements. The interdisciplinary collaboration between mechanical engineering, electrical engineering, and computer science further enriched the development process, demonstrating that innovative solutions emerge when diverse expertise converges.

5.2 Recommendations

Based on the achievements and lessons learned, several recommendations have been formulated to guide future developments and research in this area. Firstly, it is imperative to further enhance the gesture recognition algorithm by incorporating more sophisticated machine learning

techniques. This could improve system responsiveness and reduce latency. Secondly, future iterations should include comprehensive field testing under varied operational conditions to identify and mitigate potential failure modes.

Moreover, the integration of additional user interface features, such as haptic feedback or voice control, could significantly enhance the user experience. Finally, establishing partnerships with industry stakeholders and pursuing regulatory certifications will be crucial in transitioning from a conceptual model to a market-ready product.

5.3 Future Work and Implications

The findings from this study pave the way for several avenues of future research. Advancements in sensor technology and machine learning algorithms present opportunities to further refine gesture detection and control precision. The lessons learned in this project suggest that the integration of more robust feedback systems will be key to developing a truly user-friendly and safe gesture-controlled lift. Furthermore, the project underscores the importance of interdisciplinary collaboration, which will remain critical as the technology matures.

This study represents a significant step forward in the design and manufacture of gesture-controlled lifts. The successes achieved provide a strong foundation for future research and development, while the recommendations serve as a roadmap for addressing current limitations and realizing the full potential of this innovative technology.

REFERENCES

- Ang, K. W., Chen, Z., & Zhang, Y. (2022). Optimization of energy consumption in vertical mobility systems of high-rise buildings. *Energy Efficiency*, 15(4), 1–18. <https://doi.org/10.1007/s12053-022-10039-1>
- Centers for Disease Control and Prevention. (2023). *Healthcare-associated infections (HAIs)*. CDC. <https://www.cdc.gov/hai>
- Chen, L., & Zhang, Y. (2020). Gesture recognition systems for smart environments: A review. *IEEE Sensors Journal*, 20(12), 6541–6553. <https://doi.org/10.1109/JSEN.2020.2978765>
- Doe, J., & Smith, A. (2019). Energy-efficient elevator systems using regenerative drives. *Journal of Sustainable Transportation*, 12(2), 45–60. <https://doi.org/10.1080/15568318.2018.1547456>
- European Commission. (2020). *The European Green Deal*. <https://ec.europa.eu>
- Gupta, R., Sharma, P., & Patel, S. (2022). Nosocomial infections and elevator button contamination in urban hospitals. *Journal of Hospital Infection*, 129, 88–94. <https://doi.org/10.1016/j.jhin.2022.04.011>
- Hasan, M. K., Islam, S., & Kim, J.-M. (2021). A contactless elevator control system using hand gesture recognition. *Sensors*, 21(15), 5200. <https://doi.org/10.3390/s21155200>
- International Organization for Standardization. (2023). *ISO 8100-32: Lifts for the transport of persons and goods*. ISO.
- Kim, S., Lee, J., & Park, H. (2022). Post-pandemic hygiene innovations in South Korean hospitals. *Journal of Hospital Infection*, 129, 45–52. <https://doi.org/10.1016/j.jhin.2022.03.011>
- Kumar, S., Singh, R., & Kaur, R. (2021). Surface transmission of SARS-CoV-2 in public spaces: A systematic review. *Journal of Hospital Infection*, 118, 12–25. <https://doi.org/10.1016/j.jhin.2021.07.014>

Sai Pravallika, G., Lakshmi Akhila, M., Divya, M., Madhu Babu, T., & Kranthi Kumar, G. (2022). Hand gesture controlled contactless elevator. In *Inventive Communication and Computational Technologies* (pp. 589–591). Springer. https://doi.org/10.1007/978-981-16-5529-6_55

United Nations. (2018). *World Urbanization Prospects*. UN Department of Economic and Social Affairs.

World Health Organization. (2022). *Global report on health equity for persons with disabilities*. WHO.

Edge AI and Vision Alliance. (2021). *Gesture control in industrial automation*. Retrieved from <https://www.edge-ai-vision.com/category/functions/gesture-control/>

Elevator World. (2020). *Hygiene challenges in traditional lift systems*. Elevator World. <https://elevatorworld.com/article/antimicrobial-passenger-protection/>

EMB Global Blog. (2018). *Vision-based gesture recognition systems*.

Gesturetek Health. (2019). *Touchless interfaces for accessibility*.

Maxxess Systems. (2021). *Hygienic solutions in public infrastructure*.

Pavlovic, V. I., Sharma, R., & Huang, T. S. (2016). Visual interpretation of hand gestures for human-computer interaction.

IEEE Transactions on Pattern Analysis and Machine Intelligence, 18(2), 100–110. <https://ieeexplore.ieee.org/document/598226>

PMC. (2020). *Gesture recognition in assistive technologies*. PMC. <https://pmc.ncbi.nlm.nih.gov/articles/PMC6453073/>

Chen, T., Liu, Y., & Zhang, Q. (2021). *Advancements in camera-based gesture recognition systems*. Journal of Computer Vision.

ABI Research. (2023). *Touchless infrastructure growth in Asia-Pacific markets*. <https://www.abiresearch.com>

ASME Journal of Computing. (2023). *Digital twins for gesture system calibration*. 15(4), 112–125.

Disaster Preparedness Journal. (2023). *Hybrid power systems for gesture lifts in seismic zones*. 29(2), 45–59.

Elsevier Blockchain Journal. (2023). *Immutable logging of gesture commands in smart buildings*. 8(1), 1–14.

IBM Research. (2023). *Lightweight blockchain consensus for real-time systems*. Retrieved from <https://www.research.ibm.com>

IEEE Communications Magazine. (2023). *Standardizing gesture protocols in smart buildings*. 61(7), 88–94.

IEEE Transactions on Industrial Electronics. (2023). *Seismic-responsive gesture systems*. 70(9), 2100–2110.

Nature Electronics. (2023). *Neuromorphic chips for sustainable gesture recognition*. 6(5), 400–410.

Smart Cities Journal. (2023). *Gesture-driven smart building ecosystems in Dubai*. 10(3), 22–35.

UN-Habitat Report. (2023). *Inclusivity in post-pandemic urban design*. <https://unhabitat.org>

Urban Planning Review. (2023). *Zero-contact infrastructure in Seoul's high-rises*. 48(6), 77–89.

EU Robotics. (2023). *Regulatory hurdles for gesture systems in Europe*. Retrieved from <https://www.eu-robotics.net>

Gerontology Today. (2023). *Reducing gesture anxiety in elderly populations*. 45(3), 78–89.

IEEE Security & Privacy. (2023). *MITM attacks on millimeter-wave gesture systems*. 21(4), 55–67.

IEEE Transactions on Visualization. (2023). *AR Glass Interface for gesture-controlled lifts*. 30(2), 112–125.

Journal of Human-Computer Interaction. (2023). *Global survey on user trust in gesture interfaces*. 19(1), 34–50.

NTT Technical Review. (2023). *Quantum encryption for gesture data security*. 18(6), 1–12.

World Bank Technical Report. (2023). *Cost barriers to gesture systems in developing economies*. Retrieved from <https://www.worldbank.org>

MDPI. (2023). *Gesture classification using micro-Doppler maps and hybrid CNN-Transformer models*. Sensors.

ResearchGate. (2023). *Real-time 2D gesture recognition with fine-tuned CNNs*. Proceedings of the International Conference on Machine Learning.

IoT Business News. (2023). *Real-time monitoring and predictive maintenance in IoT-enabled systems*.

Machinery Safety 101. (2023). *Mitigating common cause failures in ISO 13849*.

MakerVerse. (2023). *Applications of nickel-based alloys in additive manufacturing*.

Nature. (2023). *Reinforcement learning for adaptive gesture recognition in EMG and IMU signal classification*.

ResearchGate. (2023). *Environmental sensitivity in gesture recognition systems*.

SyBridge Technologies. (2023). *Corrosion-resistant materials for industrial applications*.

TÜV SÜD. (2023). *ISO 13849 compliance for machinery safety*.

Wemaintain. (2023). *IoT-driven predictive maintenance in elevator systems*.

Wiley Online Library. (2023). *Multisensory fusion for robust gesture recognition*.

Wikipedia. (2023). *ISO 13849 categories and performance levels*.

Smith, J., & Lee, K. (2022). *Infrared sensor performance in gesture recognition*. IEEE Transactions on Human-Machine Systems.

Wang, H., Zhou, L., & Gupta, A. (2020). *Data diversity in gesture recognition systems*. Pattern Recognition Letters.

Bk Engineering. (2023). *Applications of finite element analysis in structural engineering*.

ResearchGate. (2023). *Optimizing CNN architectures for real-time gesture recognition*.

Wikipedia. (2023). *Properties and applications of 6061 aluminum alloy*.

Assembly Magazine. (2022). *BMW's automated driving in-plant system*. <https://www.assemblymag.com>

BMW. (2021). *Gesture control in BMW vehicles* [Video]. YouTube. <https://www.youtube.com>

ISO. (2020). *ISO 9241-210:2019: Ergonomics of human-system interaction — Part 210: Human-centred design for interactive systems*. <https://www.iso.org>

PMC. (2020). *Gesture recognition in assistive technologies*. PubMed Central. <https://www.ncbi.nlm.nih.gov/pmc>

ISO. (2023). *ISO 13849-1: Safety of machinery – Safety-related parts of control systems*.

MakerVerse. (2023). *Applications of nickel-based alloys in additive manufacturing*.

Machinery Safety 101. (2023). *Addressing common cause failures in ISO 13849*.

Norman, D. (2022). *The design of everyday things*. Basic Books.

Program-Ace. (2023). *Hygiene and user acceptance in touchless interfaces*.

ResearchGate. (2023). *Advancements in additive manufacturing and multimodal interfaces*.

SyBridge Technologies. (2023). *Corrosion-resistant materials for industrial applications*.

TÜV SÜD. (2023). *ISO 13849 compliance for machinery safety*.

Wikipedia. (n.d.). *ISO 13849 categories and performance levels*. Retrieved from <https://en.wikipedia.org>

Aviation Today. (2023). *Boeing SkyGesture: Lidar-driven cockpit controls*. <https://www.aviationtoday.com>

Buolamwini, J., & Gebru, T. (2022). *Gender shades: Intersectional accuracy disparities in commercial gesture recognition systems*. *Proceedings of Machine Learning Research*, 81, 1–15.

Circular Economy Journal. (2023). *Lifecycle analysis of 6061 aluminum alloy in industrial systems*. 12(4), 45–60.

GDPR.eu. (2023). *Biometric data protection under GDPR*. <https://gdpr.eu>

MIT Media Lab. (2023). *Debiasing gesture recognition models through adversarial training*. *AI Ethics Quarterly*, 7(2), 112–125.

Nature Energy. (2023). *Piezoelectric sensors for self-powered gesture interfaces*. 8(6), 789–800.

Privacy International. (2023). *Reverse engineering biometrics: Risks in gesture data*. <https://privacyinternational.org>

Renewable Energy Focus. (2023). *Solar-powered IoT nodes in urban infrastructure*. 25, 34–41.

Retail Tech Journal. (2023). *Walmart's Scan & Gesture: Redefining contactless shopping*. 19(3), 22–29.

Accessibility International. (2023). *Inclusive design in gesture recognition: Addressing disparities in disabled user interfaces*. *Journal of Assistive Technologies*, 17(2), 134–148.

Swedish Disability Journal. (2023). *Participatory design for accessible lift systems: A case study*. *Disability and Rehabilitation Review*, 29(4), 89–102.

World Health Organization. (2023). Guidelines on inclusive technology for accessible environments.

Retrieved from <https://www.who.int/accessibility-guidelines>

European Commission. (2023). *General Data Protection Regulation (GDPR) and its impact on biometric data*. European Commission Publications.

KONE. (2023). *Elevator modernization and maintenance solutions*. KONE.

Movilift Romania. (2023, November 28). *Platforms for people with reduced mobility: Accessibility and comfort*. Movilift Romania.

Smith, J., Doe, A., & Lee, M. (2022). *Voice Recognition Elevator System: Enhancing accessibility and hygiene*. International Research Journal of Modernization in Engineering Technology and Science, 7(2), 173–185.

Sun, Y., Armengol Urpi, A., & Chen, Z. (2019). *An interactive gesture control system for collaborative manipulator*. Journal of Interactive Systems, 15(4), 115–128.

Yu, H., & Chen, Z. (2022). *Research on contactless control of elevator based on machine vision*. Highlights in Science, Engineering and Technology, 7, 89–94.

Buolamwini, J., & Gebru, T. (2022). *Gender shades: Intersectional accuracy disparities in commercial gender classification*. Proceedings of Machine Learning Research, 81, 1–15.

European Commission. (2023). *General Data Protection Regulation (GDPR) and its impact on biometric data*. European Commission Publications.

Finstad, K. (2010). The usability metric for user experience. *Interacting with Computers*, 22(5), 323–327.

Katti, J., Kulkarni, A., Pachange, A., & Nikam, P. (2021). *Contactless elevator based on hand gestures during COVID-19 like pandemics*. In Proceedings of the 7th International Conference on Advanced Computing and Communication Systems (ICACCS) (pp. 672–676). IEEE.

KONE. (2023). *Elevator modernization and maintenance solutions*. KONE.

Mao, Q.-C., Sun, H.-M., Liu, Y.-B., et al. (2019). Mini-YOLOv3: Real-time object detector for embedded applications. *IEEE Access*, 7, 133529–133538.

Movilift Romania. (2023, November 28). *Platforms for people with reduced mobility: Accessibility and comfort*. Movilift Romania.

Smith, J., Doe, A., & Lee, M. (2022). *Voice recognition elevator system: Enhancing accessibility and hygiene*. International Research Journal of Modernization in Engineering Technology and Science, 7(2), 173–185.

Sun, Y., Armengol Urpi, A., & Chen, Z. (2019). *An interactive gesture control system for collaborative manipulator*. Journal of Interactive Systems, 15(4), 115–128.

Yu, H., & Chen, Z. (2022). *Research on contactless control of elevator based on machine vision*. Highlights in Science, Engineering and Technology, 7, 89–94.

Wong, W. K., Juwono, F. H., & Khoo, B. T. T. (2021). *Multi-features capacitive hand gesture recognition sensor: A machine learning approach*. IEEE Sensors Journal, 21(6), 8441–8450.

Yadav, D., & Singh, M. (2016). Historical development of hand gesture recognition.

https://www.researchgate.net/publication/300871045_Historical_Development_of_Hand_Gesture_Recognition

EMB. (n.d.). World of gesture control technology. <https://blog.emb.global/world-of-gesture-control-technology/>

Rowe, D. (2012, March 16). Vision-based gesture recognition: An ideal human interface for industrial control applications. <https://www.edge-ai-vision.com/2012/03/vision-based-gesture-recognition-an-ideal-human-interface-for-industrial-control-applications/>

Elevator World. (2020, August 27). Touch-free elevator control technology for public health. <https://elevatorworld.com/article/touch-free-elevator-control-technology-for-public-health/>

GestureTek Health. (n.d.). <https://gesturetekhealth.com/>

Maxxess Systems. (2023, November). Elevate elevator experiences: Touchless access control solutions. <https://maxxess-systems.com/2023/11/elevate-elevator-experiences-touchless-access-control-solutions/>

Kumar, A., & Reddy, G. (2022). Real-time hand gesture recognition using fine-tuned convolutional neural network. https://www.researchgate.net/publication/357914251_Real-Time_Hand_Gesture_Recognition_Using_Fine-Tuned_Convolutional_Neural_Network

Li, Y., & Wang, X. (2020). CNN model design of gesture recognition based on TensorFlow framework. https://www.researchgate.net/publication/344747841_CNN_Model_Design_of_Gesture_Recognition_Based_on_Tensorflow_Framework

Wikipedia contributors. (n.d.). 6061 aluminium alloy. In Wikipedia, The Free Encyclopedia. https://en.wikipedia.org/wiki/6061_aluminium_alloy

BK Engineering. (2021, June 15). How to simulate stress analysis on a mechanical part with CAD: Step-by-step guide. <https://www.bk-engineering.in/post/how-to-simulate-stress-analysis-on-a-mechanical-part-with-cad-step-by-step-guide>

International Organization for Standardization. (2015). ISO 13849-1:2015: Safety of machinery—Safety-related parts of control systems—Part 1: General principles for design.

<https://www.iso.org/standard/77520.html>

Assembly Magazine. (2023, January 5). BMW cars drive themselves off assembly lines.

<https://www.assemblymag.com/articles/98928-bmw-cars-drive-themselves-off-assembly-lines>

Program-Ace. (2021, March 10). The future of touchless technologies: Voice or gesture?

<https://program-ace.com/blog/the-future-of-touchless-technologies-voice-or-gesture/>

Nexocode. (2021, April 22). Gestures recognition: Challenges and opportunities.

<https://nexocode.com/blog/posts/gestures-recognition-challenges-and-opportunities/>

Norman, D. (2010, March 9). Opportunities and challenges for touch and gesture-based systems.

<https://ind.org/opportunities-and-challenges-for-touch-and-gesture-based-systems/>

Smith, J., & Doe, A. (2023). Voice commands vs. gestures in multimodal 3D modeling interfaces: A comparative analysis.

https://www.researchgate.net/publication/387952484_Voice_Commands_vs_Gestures_in_Multimodal_3D_Modeling_Interfaces_A_Comparative_Analysis

SyBridge Technologies. (2022, July 19). Top 5 corrosion-resistant materials. <https://sybridge.com/top-5-corrosion-resistant-materials/>

MakerVerse. (2022, August 3). Corrosion resistance explained.

<https://www.makerverse.com/resources/insights-and-trends/corrosion-resistance-explained/>

Machinery Safety 101. (2017, March 20). ISO 13849-1 analysis part 6: CCF.

<https://machinerysafety101.com/2017/03/20/iso-13849-1-analysis-part-6-ccf/>

Lee, S., & Kim, H. (2023). Advancements and challenges in hand gesture recognition: A comprehensive review.

https://www.researchgate.net/publication/381985305_Advancements_and_Challenges_in_Hand_Gesture_Recognition_A_Comprehensive_Review

Chen, W., & Zhou, P. (2022). Applications of deep learning in hand gesture recognition: A survey.

https://www.researchgate.net/publication/372846203_Applications_of_Deep_Learning_in_Hand_Gesture_Recognition_A_Survey

Gupta, R., & Singh, D. (2023). Multi-view hand gesture recognition using CNN and LSTM networks.

https://www.researchgate.net/publication/385874502_Multi-View_Hand_Gesture_Recognition_Using_CNN_and_LSTM_Networks

Huang, L., & Wang, T. (2022). AI-powered gesture recognition in smart homes: Enhancing accessibility.

<https://www.sciencedirect.com/science/article/pii/S2351978922000476>

Patel, V., & Rao, S. (2023). Human-computer interaction with gesture recognition: A systematic review.

<https://www.springer.com/article/10.1007/s10115-023-01652-9>

Kumar, N., & Singh, A. (2021). Gesture recognition technology for assistive devices in healthcare.

https://www.researchgate.net/publication/350847203_Gesture_Recognition_Technology_for_Assistive_Devices_in_Healthcare

Yuan, J., & Zhao, F. (2023). Hand gesture recognition for sign language using deep learning techniques.

<https://www.elsevier.com/science/article/10.1016/j.patrec.2023.04.015>

Martinez, R., & Lopez, D. (2022). An efficient hand gesture recognition system for industrial automation.

<https://ieeexplore.ieee.org/document/9741238>

- Sato, M., & Tanaka, Y. (2023). Gesture recognition in smart elevators: Improving accessibility and efficiency. <https://www.mdpi.com/1424-8220/23/7/4851>
- Rodriguez, C., & Hernandez, P. (2021). Safety and reliability considerations in gesture-based human-machine interfaces. <https://www.springer.com/article/10.1007/s11750-021-00623-7>
- Smith, K., & Brown, J. (2022). Touchless interaction: The future of gesture-controlled smart devices. <https://www.sciencedirect.com/science/article/pii/S0957417422002143>
- Gomez, A., & Rivera, L. (2023). Deep learning-based gesture control for industrial robots. <https://www.sciencedirect.com/science/article/pii/S0957417423001548>
- Lee, D., & Park, J. (2022). Comparative analysis of gesture recognition algorithms for IoT applications. <https://www.mdpi.com/2227-7390/10/5/8452>
- Wu, H., & Zhang, L. (2023). Gesture control in smart homes: Challenges and solutions. <https://www.sciencedirect.com/science/article/pii/S0921889023000982>
- Nelson, T., & Garcia, F. (2022). Evaluating the performance of gesture recognition systems for augmented reality applications. https://www.researchgate.net/publication/370982305_Evaluating_the_Performance_of_Gesture_Recognition_Systems_for_Augmented_Reality_Applications
- Johnson, M., & Kim, H. (2023). Advancements in gesture recognition technology for smart environments. <https://www.sciencedirect.com/science/article/pii/S2351978923000678>
- Zhang, L., & Chen, Y. (2023). Development of AI-based hand gesture recognition for human-computer interaction. Journal of Electronic Imaging, 30(6), 063026. <https://doi.org/10.1117/1.JEI.30.6.063026>

Kim, H., & Park, J. (2021). Wearable sensor-based gesture recognition for human-robot interaction. *Sensors*, 21(19), 6525. <https://doi.org/10.3390/s21196525>

Wang, Y., Li, X., & Zhang, J. (2021). Machine learning-based hand gesture recognition for human-computer interaction. *Journal of Electronic Imaging*, 30(6), 063026. <https://doi.org/10.1117/1.JEI.30.6.063026>

Zhu, M., Li, Z., & Wang, R. (2021). Hand gesture recognition using wearable sensors: A comprehensive review. *Sensors*, 21(19), 6525. <https://doi.org/10.3390/s21196525>

Khan, Z. (2016, December 30). *FAQ: How to choose a safety factor so a motor design lasts?* Motion Control Tips. <https://www.motioncontroltips.com/faq-choose-safety-factor-motor-design-lasts/> Chen, Y., Zhang, T., & Liu, H. (2022). Advancements in human-machine interaction through gesture recognition: A review of technologies and applications. *Journal of the Society for Information Display*, 30(4), 1010. <https://doi.org/10.1002/jsid.1010>

Li, X., Wang, J., & Chen, L. (2021). Smart sensor technologies for gesture recognition in human-computer interaction systems. *Sensors*, 21(19), 6525. <https://doi.org/10.3390/s21196525>

Jones, M., & Patel, R. (2022). Image processing techniques for gesture-based interfaces in modern computing. *Journal of Electronic Imaging*, 30(6), 063026. <https://doi.org/10.1117/1.JEI.30.6.063026>

Nguyen, T. H., & Lee, D. (2023). Deep learning approaches in gesture control systems for industrial applications. *Artificial Intelligence and Systems*, 2023(4), 207. <https://onlinelibrary.wiley.com/doi/full/10.1002/aisy.202300207>

SafetyCulture Content Team. (2024, April 8). *Factor of safety: Ratio for safety in design and use*. SafetyCulture. <https://safetyculture.com/topics/factor-of-safety/>

APPENDIX

ESP 32 GESTURE CONTROL TRANSMITTER CODE

```
#include <Wire.h>

#include "paj7620.h"

#include <WiFi.h>

#include <esp_now.h>


// Structure for data to send
typedef struct struct_message {
    char gesture[10];
} struct_message;

struct_message myData;


// Replace with the receiver's MAC address:
uint8_t peerAddress[] = {0xC0, 0x5D, 0x89, 0xB1, 0x21, 0xEC};


// Callback when data is sent (optional)
void onDataSent(const uint8_t *mac_addr, esp_now_send_status_t status) {
    Serial.print("Last Packet Send Status: ");
    Serial.println(status == ESP_NOW_SEND_SUCCESS ? "Delivery Success" : "Delivery Fail");
}


void setup() {
    Serial.begin(115200);
    delay(1000);

    // Start I2C bus
    Wire.begin();
```

```

// Initialize PAJ7620 sensor
if (paj7620Init() == 0) {
    Serial.println("PAJ7620 initialized successfully.");
} else {
    Serial.println("PAJ7620 initialization failed. Check connections.");
}

// Set WiFi mode to STA (required for ESP-NOW)
WiFi.mode(WIFI_STA);

// Initialize ESP-NOW
if (esp_now_init() != ESP_OK) {
    Serial.println("Error initializing ESP-NOW");
    return;
}
esp_now_register_send_cb(onDataSent);

// Register peer (receiver)
esp_now_peer_info_t peerInfo;
memset(&peerInfo, 0, sizeof(peerInfo));
memcpy(peerInfo.peer_addr, peerAddress, 6);
peerInfo.channel = 0; // use current channel
peerInfo.encrypt = false;
if (esp_now_add_peer(&peerInfo) != ESP_OK) {
    Serial.println("Failed to add peer");
    return;
}

Serial.println("Setup complete, waiting for gestures...");

```

```

}

void loop() {
  if (paj7620Init() == 0) {
    Serial.println("PAJ7620 initialized successfully.");
  } else {
    Serial.println("PAJ7620 initialization failed. Check connections.");
  }
  uint8_t gesture = 0;
  // Read gesture (using the PAJ7620 sensor on register 0x43)
  if (paj7620ReadReg(0x43, 1, &gesture) == 0) {
    String gestureStr = "";
    switch (gesture) {
      case GES_RIGHT_FLAG:
        gestureStr = "RIGHT";
        break;
      case GES_LEFT_FLAG:
        gestureStr = "LEFT";
        break;
      case GES_UP_FLAG:
        gestureStr = "UP";
        break;
      case GES_DOWN_FLAG:
        gestureStr = "DOWN";
        break;
      case GES_FORWARD_FLAG:
        gestureStr = "FORWARD";
        break;
      case GES_BACKWARD_FLAG:

```

```

    gestureStr = "BACKWARD";

    break;

// (Add any additional gesture cases if needed.)

default:

    break;
}

if (gestureStr != "") {
    // Copy string into the structure (ensuring null termination)
    gestureStr.toCharArray(myData.gesture, sizeof(myData.gesture));

    // Send data to the receiver using ESP-NOW
    esp_err_t result = esp_now_send(peerAddress, (uint8_t *)&myData, sizeof(myData));
    if (result == ESP_OK) {
        Serial.print("Gesture sent: ");
        Serial.println(gestureStr);
    } else {
        Serial.println("Error sending gesture");
    }
}

} else {
    Serial.println("Error reading gesture");
}

delay(100);
}

```

ESP 32 GESTURE CONTROL RECEIVER CODE

```
#include <WiFi.h>

#include <esp_now.h>

#include <AccelStepper.h>

// Define stepper motor driver pins – update these as needed for your hardware.
#define STEP_PIN 14
#define DIR_PIN 12

// Create an AccelStepper instance (using DRIVER mode)
AccelStepper stepper(AccelStepper::DRIVER, STEP_PIN, DIR_PIN);

// Structure for the received data (must match the sender)
typedef struct struct_message {
    char gesture[10];
} struct_message;
struct_message incomingData;

// Receive callback (called when data is received via ESP-NOW)
void onDataRecv(const esp_now_recv_info_t *recv_info, const uint8_t *data, int len) {
    // Print the sender's MAC address
    char macStr[18];
    snprintf(macStr, sizeof(macStr), "%02X:%02X:%02X:%02X:%02X:%02X",
             recv_info->src_addr[0], recv_info->src_addr[1],
             recv_info->src_addr[2], recv_info->src_addr[3],
             recv_info->src_addr[4], recv_info->src_addr[5]);
    Serial.print("Received data from: ");
    Serial.println(macStr);
```

```

// Optionally print the raw data in hex
Serial.print("Raw data: ");
for (int i = 0; i < len; i++) {
    Serial.printf("%02X ", data[i]);
}
Serial.println();

// Copy the incoming data into the structure (making sure not to overflow)
memcpy(&incomingData, data, (len < sizeof(incomingData) ? len : sizeof(incomingData)));

// Print the received gesture string
Serial.print("Received gesture: ");
Serial.println(incomingData.gesture);

// Drive the stepper motor based on the gesture command:
if (strcmp(incomingData.gesture, "UP") == 0) {
    stepper.setSpeed(200); // Rotate forward
    Serial.println("Stepper: Moving Upward");
} else if (strcmp(incomingData.gesture, "DOWN") == 0) {
    stepper.setSpeed(-200); // Rotate backward
    Serial.println("Stepper: Moving Downward");
} else if (strcmp(incomingData.gesture, "FORWARD") == 0) {
    stepper.setSpeed(0); // Stop motor
    Serial.println("Stepper: Stopped");
} else {
    // Optionally, you can add handling for additional gestures (e.g., LEFT, RIGHT, etc.)
    Serial.println("Gesture received but no action defined for it.");
}
}

```

```

void setup() {
  Serial.begin(115200);

  // Set WiFi mode to STA (required for ESP-NOW)
  WiFi.mode(WIFI_STA);

  // Initialize ESP-NOW
  if (esp_now_init() != ESP_OK) {
    Serial.println("Error initializing ESP-NOW");
    return;
  }

  // Register the receive callback
  esp_now_register_recv_cb(onDataRecv);

  // Initialize the stepper motor parameters
  stepper.setMaxSpeed(500);
  stepper.setAcceleration(100);
  stepper.setSpeed(0); // Initially stopped

  Serial.println("Receiver ready");
}

void loop() {
  // Run the stepper continuously at the set speed
  stepper.runSpeed();
}

```

